

Complex-valued Deng Entropy

Authors: Lipeng Pan, Yong Deng, Yong Deng

Date: 2021-06-03T00:00:00+00:00

Abstract

Complex evidence theory has been applied to several fields due to its advantages in modeling and processing uncertain information. However, to measure the uncertainty of the complex mass function is still an open issue. The main contribution of this paper is to propose a complex-valued Deng entropy. The complex-valued Deng entropy can effectively measure the uncertainty of the mass function in the complex-valued framework. Meanwhile, the complex-valued Deng entropy is a generalization of the Deng entropy and Shannon entropy. That is, the complex-valued Deng entropy can degenerate to classical Deng entropy when the complex-valued mass function degenerates to a mass function in real space. In addition, the proposed complex-valued Deng entropy can also degenerate to Shannon entropy when the complex-valued mass function degenerates to a probability distribution in real space. Some numerical examples demonstrate the compatibility and effectiveness of the complex-valued Deng entropy.

Full Text

Preamble

Complex-valued Deng Entropy

Lipeng Pan^a, Yong Deng^{a,b,c,d,*}

^aInstitute of Fundamental and Frontier Science, University of Electronic Science and Technology of China, Chengdu, 610054, China

^bSchool of Education, Shannxi Normal University, Xi'an, 710062, China

^cSchool of Knowledge Science, Japan Advanced Institute of Science and Technology, Nomi, Ishikawa 923-1211, Japan

^dDepartment of Management, Technology, and Economics, ETH Zürich, Zurich, Switzerland

Abstract

Complex evidence theory has been applied to several fields due to its advantages in modeling and processing uncertain information. However, measuring the uncertainty of the complex mass function remains an open issue. The main contribution of this paper is to propose a complex-valued Deng entropy. The complex-valued Deng entropy can effectively measure the uncertainty of the mass function in the complex-valued framework. Meanwhile, the complex-valued Deng entropy is a generalization of the Deng entropy and Shannon entropy. That is, the complex-valued Deng entropy can degenerate to classical Deng entropy when the complex-valued mass function degenerates to a mass function in real space. In addition, the proposed complex-valued Deng entropy can also degenerate to Shannon entropy when the complex-valued mass function degenerates to a probability distribution in real space. Some numerical examples demonstrate the compatibility and effectiveness of the complex-valued Deng entropy.

Keywords: complex-valued mass function, Deng entropy, complex-valued Deng entropy, Shannon entropy, uncertain information

*Corresponding author

Email address: prof.deng@hotmail.com; dengentropy@uestc.edu.cn (Yong Deng)

Preprint submitted to Elsevier June 3, 2021

1. Introduction

How to model and process uncertain information has received increasing attention, and a number of theories have been developed, such as probability theory [?], fuzzy set [?], intuitionistic fuzzy set [?], pythagorean fuzzy set [?], and rough sets [?]. Among these theories, probability theory is fundamental to most theoretical studies and practical applications [?, ?, ?, ?]. Faced with complex problems, probability is extended from real to complex spaces. For example, researchers introduced complex-valued probability into quantum mechanics and quantum game theory to describe interference phenomena [?, ?].

Moreover, as another extension of probability theory, the Dempster-Shafer evidence theory [?, ?] has its own advantages: the support degree of propositions in evidence theory is not point estimation but interval estimation, and the support degree of correct propositions is further improved after Dempster combination rule. These advantages lead to the wide application of evidence theory in the fields of decision making [?, ?], risk analysis [?], pattern recognition [?], target clustering [?] and other hybrid methods [?, ?].

Recently, Pan and Deng proposed a complex-valued evidence theory by introducing the phase angle into the mass function, and defined the Dempster combination rule in the complex-valued framework [?]. In the framework of complex-valued evidence theory, it is experimentally demonstrated based on the data set that the complex-valued mass function is more reasonable for modeling

uncertain information. This work promotes the application of complex-valued evidence theory in engineering; however, there is no mention of uncertainty measurements of complex-valued mass functions in complex-valued evidence theory. Therefore, how to reasonably measure the uncertainty of the complex-valued mass function remains an open issue.

In this paper, we propose a generalized Deng entropy, named complex-valued Deng entropy, which fully considers the effect of phase angle in support and can effectively measure the uncertainty for the complex-valued mass function. Concurrently, it is compatible with classical Deng entropy and Shannon entropy; i.e., when the complex-valued mass function degenerates to a real-valued mass function, the complex-valued Deng entropy degenerates to classical Deng entropy or Shannon entropy. Some numerical examples explain the compatibility and effectiveness of the complex-valued Deng entropy.

The remaining work is organized as follows. Section 2 introduces the knowledge of the complex-valued mass function and Deng entropy. Complex-valued Deng entropy is presented in Section 3. In Section 4, some numerical examples to explain the compatibility and effectiveness of complex-valued Deng entropy are presented. Section 5 summarizes the work.

2. Preliminaries

In this section, the related concepts of complex-valued mass function and Deng entropy are introduced.

2.1. Complex-valued mass function

In this subsection, we introduce the concept of complex-valued mass function and mass function, and the relationship between them.

Definition II.1 (Frame of discernment) [?, ?]

Suppose there exists a positive definite, non-negative, mutually exclusive set (cid:9), denoted as frame of discernment, whose power set is described as follows:

$$E = \{\emptyset, \{E_1\}, \{E_2\}, \dots, \{E_n\}, \{E_1, E_2\}, \dots, E\}$$

Definition II.2 (Complex-valued mass function) [?]

There exists a mapping function from 2^E to $[0, 1]$ such that $|CM| : 2^E \rightarrow [0, 1]$ where $|CM|$ is the modulus of the complex-valued CM . CM satisfies $CM(\emptyset) = 0$, $\sum |CM(A)| = 1$, and $CM(A) = M(A)e^{i\pi\theta_A} = x_A + iy_A$. $CM(A)$ is the support degree for the proposition, named as complex-valued mass function, and $\pi\theta_A$ is the phase angle, satisfying $\pi\theta_A \in [-\pi, \pi]$, that is, $\theta_A \in [-1, 1]$.

Definition II.3 (Mass function) [?, ?]

For a map M from 2^E to $[0, 1]$, that is, $|M| : 2^E \rightarrow [0, 1]$, and satisfies $M(\emptyset) = 0$, $\sum M(A) = 1$. $M(A)$ is denoted as mass function, which indicates the support degree of the evidence for proposition A . Obviously, $M(A)$ is a special case of

$CM(A)$; i.e., when $\theta_A = 0$, $CM(A)$ degenerates to a mass function $M(A)$ of real-valued space.

2.2. Deng entropy

Benefiting from the application of Shannon entropy in uncertainty measurement under a probability distribution framework, several researchers have proposed uncertainty measures for real-valued mass functions in evidence theory, such as Dubois and Prade's weighted Hartley entropy [?], Hohle's confusion measure [?], Yager's dissonance measure [?], Deng entropy [?] and others [?, ?, ?]. These entropies can effectively measure uncertain information and thus are widely studied and applied in various fields. Taking Deng entropy as an example, Abellán analyzed the five properties of Deng entropy [?], Kang et al. analyzed the distribution of maximum Deng entropy [?], Liu et al. established the relationship between Deng entropy and other non-additive entropies [?], Moral-García et al. critiqued the Deng entropy and proposed maximum of entropy for belief intervals [?, ?], Deng proposed information volume of mass function based on fractal idea based on Deng entropy [?], Buono and Longobardi proposed the dual entropy of Deng entropy [?], Pan et al. introduced the idea of power-law fractal of maximum Deng entropy in the correlation coefficient to solve the conflict problem between evidences [?], Liao et al. introduced Deng entropy in the decision-making process to the selection of effective drugs for COVID-19 [?], Boukaboul and Boukaboul applied Deng entropy to IoT decision-making [?], Zhou et al. proposed the multiple attribute decision-making method based on Deng entropy [?], and Kazemi et al. analyzes the fractional law of Deng entropy and discusses its application [?].

Thus, it is defined as follows.

Definition II.4 (Deng entropy) [?]

Consider a frame of discernment E , M is a mass function, whose uncertainty measure is described as follows:

$$E_d = - \sum M(A) \ln \frac{M(A)}{2^{|A|} - 1}$$

where $|A|$ is the cardinality of A . The Deng entropy is an extension of the Shannon entropy, and when $|A| = 1$, the Deng entropy degenerates to the Shannon entropy. The form of the Shannon entropy is described as follows.

Definition II.5 (Shannon entropy) [?]

For a probability distribution P in the frame of discernment E , its uncertainty measure is as follows:

$$E_d = - \sum p(A) \ln p(A)$$

where $p(A)$ is the probability of event A . The $p(A)$ is a special case of $M(A)$; when $|A| = 1$, $M(A)$ and $p(A)$ are equivalent.

3. New entropy for complex-valued mass function

The methods in Subsection 2.2 have their own advantages in measuring the uncertainty of the mass function. However, these works cannot effectively measure the uncertainty for the complex-valued mass function; therefore, it remains an open issue. In this work, a complex-valued uncertainty measure, called complex-valued Deng entropy, is presented as follows:

Definition III.1 (complex-valued Deng entropy)

$$CE_d = - \sum |M(A)e^{i\pi\theta_A}| \ln \frac{|M(A)e^{i\pi\theta_A}|}{2^{|A|} - 1}$$

where $|M(A)e^{i\pi\theta_A}|$ is the modulus of $M(A)e^{i\pi\theta_A}$, and $|A|$ is the number of elements in proposition A , also noted as the cardinality of A .

Further, the complex-valued Deng entropy can be re-expressed as:

$$CE_d = - \sum [|M(A)e^{i\pi\theta_A}| \ln M(A) + |M(A)e^{i\pi\theta_A}| \ln e^{i\pi\theta_A} - |M(A)e^{i\pi\theta_A}| \ln(2^{|A|} - 1)]$$

Next, we organize the complex-valued Deng entropy:

$$CE_d = \left| \sum [-M(A) \ln M(A) + iM(A)\pi\theta_A - M(A) \ln(2^{|A|} - 1)] \right|$$

Obviously, the complex-valued Deng entropy is very similar to the classical Deng entropy and Shannon entropy, and the relationship between them is described as follows:

- (i) When $\theta_A = 0$, the complex-valued Deng entropy degenerates to the classical Deng entropy, i.e.,

$$CE_d = \left| - \sum M(A) \ln M(A) - \sum M(A) \ln(2^{|A|} - 1) \right|$$

- (ii) For arbitrary $|A| = 1$, the complex-valued Deng entropy degenerates to the complex-valued Shannon entropy:

$$CE_d = CH = \left| - \sum (M(A) \ln M(A) + iM(A)\pi\theta_A) \right|$$

where CH represents complex-valued Shannon entropy.

- (iii) For arbitrary $|A| = 1$ and $\theta_A = 0$, the complex-valued Deng entropy degenerates to the Shannon entropy:

$$CE_d = - \sum M(A) \ln M(A)$$

4. Numerical examples

In this section, some examples are designed to explain the compatibility and effectiveness of the complex-valued Deng entropy.

Example 3.1

Suppose there is a complex-valued mass function $CM(E_1) = 1$, whose uncertainty information is measured as follows:

$$\begin{aligned} H &= -1 \times \ln 1 = 0 \\ CH &= -1 \times \ln 1 = 0 \\ E_d &= -1 \times \ln \frac{1}{2^{|I|} - 1} \\ CE_d &= -1 \times \ln \frac{1}{2^{|I|} - 1} \end{aligned}$$

This example shows that for a perfectly certain proposition, the uncertainty measure is 0 based on H , CH , E_d and CE_d , which is intuitive.

Example 3.2

Consider a frame of discernment $E = \{E_1, E_2, E_3, E_4\}$, with a complex-valued mass function $CM(E_1) = CM(E_2) = CM(E_3) = CM(E_4) = \frac{1}{4}$. Its uncertainty information is measured as follows:

$$\begin{aligned} H &= - \sum \frac{1}{4} \ln \frac{1}{4} = 1.3863 \\ CH &= - \sum \frac{1}{4} \ln \frac{1}{4} = 1.3863 \\ E_d &= - \sum \frac{1}{4} \ln \frac{\frac{1}{4}}{2^{|I|} - 1} = 1.3863 \\ CE_d &= - \sum \frac{1}{4} \ln \frac{\frac{1}{4}}{2^{|I|} - 1} = 1.3863 \end{aligned}$$

Example 3.3

There is a complex-valued mass function $CM(E_1) = CM(E_2) = CM(E_3) = CM(E_4) = \frac{1}{4}e^{i\frac{3\pi}{4}}$ in the frame of discernment E . Then:

$$CE_d = \left| - \sum \frac{1}{4} \ln \frac{1}{4} + i \times 4 \times \pi \times \frac{1}{4} \right| = 3.1416$$

Examples 3.2 and 3.3 measure inaccurate information in real-valued space and complex-valued space, respectively. It is reasonable to see from the results that

adding the phase angle leads to an increase in uncertain information in the complex-valued framework. This also shows the conditions for the application of CH and H .

Example 3.4

Consider a frame of discernment $E = \{E_1, E_2, E_3, E_4\}$, for a complex-valued mass function $CM(E) = 1$, which has the following uncertainty:

$$\begin{aligned} H &= -1 \times \ln 1 = 0 \\ CH &= -1 \times \ln 1 = 0 \\ E_d &= -1 \times \ln \frac{1}{2^{|4|} - 1} = 2.7081 \\ CE_d &= -1 \times \ln \frac{1}{2^{|4|} - 1} = 2.7081 \end{aligned}$$

In contrast to $CM(E_1) = 1$, $CM(E) = 1$ indicates that for propositions that are completely unknown, in Example 3.1, $H = 0$ and $CH = 0$. In Example 3.4, it is still $H = 0$ and $CH = 0$. Obviously, in Example 3.4, the results for H and CH are not reasonable, indicating that H and CH are more applicable to probability distributions than to mass functions. For E_d and CE_d , the measures in both examples are intuitive, which indicate that E_d and CE_d can be effective measures of uncertainty in mass functions, and also that E_d and CE_d are compatible with H and CH .

Example 3.5

Suppose there exists a complex-valued mass function $CM(E) = e^{i\frac{\pi}{4}}$ in $E = \{E_1, E_2, E_3, E_4\}$. Then:

$$CE_d = \left| -\ln \frac{1}{2^{|4|} - 1} + i \times \pi \times \frac{1}{4} \right| = 3.1306$$

The $CE_d = 2.7081$ and $CE_d = 3.1306$ are the results of uncertainty measurements based on complex-valued Deng entropy in the real-valued and complex-valued framework, respectively, and it is obvious that $2.7081 < 3.1306$, which is due to the uncertainty information of adding phase angles in Example 3.5. This result is intuitive and also shows that CE_d is compatible with E_d .

The examples above explain the relationship between CE_d and E_d , CH , H ; that is, CE_d is compatible with E_d , CH , and H . Next, two examples are designed to explain the effectiveness of CE_d in measuring uncertain information.

Example 3.6

Suppose there exists a frame of discernment E , with four complex-valued mass functions described as follows:

$$CM_1(E) = 1$$

$$CM_2(E) = \frac{1}{|E|}$$

$$CM_3(E) = \frac{1}{|E|}e^{i\pi}$$

$$CM_4(E) = \frac{1}{|E|}e^{i\frac{\pi}{|E|}}$$

The form of E is shown in Table 1. Figure 1 shows the uncertainty information for the four complex-valued mass functions. As can be seen in Figure 1, the uncertainty of CM_3 is larger than that of CM_2 , CM_1 , and CM_4 . This is a reasonable result because completely unknown information contains more uncertainty relative to the uncertainty information of the probability distribution. Also, there is a difference between CM_3 and CM_2 ; the phase angle also contains uncertainty information, so the uncertainty of CM_3 is larger, which is 22.4. Similarly, the uncertainty of CM_4 is larger than that of CM_2 . This example explains that the complex-valued Deng entropy can effectively measure the uncertainty for the complex-valued mass function.

[Figure 1: see original paper]

Example 3.7

Consider two complex-valued mass functions in $E = \{e_1, e_2, e_3, \dots, e_j, \dots, e_{32}\}$:

$$CM_1(E_5) = 0.05, \quad CM_1(\{E_4, E_6, E_7\}) = 0.1, \quad CM_1(E) = 0.15, \quad CM_1(X) = 0.7$$

$$CM_2(E_5) = 0.05e^{i0.2\pi}, \quad CM_2(\{E_4, E_6, E_7\}) = 0.1e^{i0.4\pi}, \quad CM_2(E) = 0.15e^{i0.6\pi}, \quad CM_2(X) = 0.7e^{i0.7\pi}$$

Table 2 lists some of the complex-valued Deng entropy values when X varies, and more information is in Figure 2. It can be seen from Table 2 that the uncertainty of CM_2 increases as the number of elements in X increases, and the complex-valued Deng entropy reaches the maximum when $X = 32$. It is worth noting that for each X , the uncertainty of CM_2 is always larger than that of CM_1 , which is intuitive. This example also demonstrates the effectiveness of the complex-valued Deng entropy.

[Figure 2: see original paper]

5. Conclusion

Most methods can effectively measure the uncertainty for the mass function in the real-valued framework; however, how to reasonably measure the uncertainty of the complex-valued mass function remains an open issue. Therefore, we propose the generalized Deng entropy, named complex-valued Deng entropy. The main contribution of the complex-valued Deng entropy is that the uncertainty of the complex-valued mass function can be effectively measured under the framework of complex-valued evidence theory. Also, complex-valued Deng entropy

has high compatibility. Some numerical examples demonstrate the compatibility and effectiveness of complex-valued Deng entropy. Thus, the new entropy provides a reliable tool to measure uncertain information. Further, we may discuss the properties of the new entropy and its physical meaning in future work.

Declaration of competing interest

The authors have no conflict of interests regarding the publication of this paper.

Acknowledgment

The work is partially supported by National Natural Science Foundation of China (Grant No. 61973332), JSPS Invitational Fellowships for Research in Japan (Short-term).

References

- [1] P.-S. Laplace, Analytical theory of probabilities, published in.
- [2] L. A. Zadeh, Fuzzy sets, in: Fuzzy sets, fuzzy logic, and fuzzy systems: selected papers by Lotfi A Zadeh, World Scientific, 1996, pp. 394–432.
- [3] K. T. Atanassov, Intuitionistic fuzzy sets, Vol. 20, Springer, 1986, pp. 87–96.
- [4] R. R. Yager, A. M. Abbasov, Pythagorean membership grades, complex numbers, and decision making, International Journal of Intelligent Systems 28 (5) (2013) 436–452.
- [5] Z. Pawlak, Rough sets, International journal of computer & information sciences 11 (5) (1982) 341–356.
- [6] L. Vervoort, Probability theory as a physical theory points to superdeterminism, Entropy 21 (9) (2019) 848.
- [7] R. Durrett, Probability: theory and examples, Vol. 49, Cambridge university press, 2019.
- [8] L. Wang, L. Ma, C. Wang, N.-g. Xie, J. M. Koh, K. H. Cheong, Identifying influential spreaders in social networks through discrete moth-flame optimization, IEEE Transactions on Evolutionary Computation.
- [9] L. P. Deng, Complex-valued renyi entropy, chinaXiv (2021) 202106.00005.
- [10] G. Baym, Lectures on quantum mechanics, CRC Press, 2018.
- [11] J. W. Lai, J. R. A. Tan, H. Lu, Z. R. Yap, K. H. Cheong, Parrondo paradoxical walk using four-sided quantum coins, Physical Review E 102 (1) (2020).
- [12] A. Dempster, Upper and lower probabilities induced by a multivalued mapping (upper and lower probabilities induced by multivalued mapping).
- [13] G. Shafer, A mathematical theory of evidence, Vol. 42, Princeton university press, 1976.
- [14] X. Gao, L. Pan, Y. Deng, Quantum pythagorean fuzzy evidence theory (qpfet): A negation of quantum mass function view, IEEE Transactions on Fuzzy Systems.

- [15] H. Abbasimehr, R. Paki, Prediction of covid-19 confirmed cases combining deep learning methods and bayesian optimization, *Chaos, Solitons & Fractals* 142 (2021) 110511.
- [16] B. Zhu, X. Zheng, H. Liu, J. Li, P. Wang, Analysis of spatiotemporal characteristics of big data on social media sentiment with covid-19 epidemic topics, *Chaos, Solitons & Fractals* 140 (2020) 110123.
- [17] D. Li, Y. Deng, K. H. Cheong, Multisource basic probability assignment fusion based on information quality, *International Journal of Intelligent Systems* 36 (4) (2021) 1851–1875.
- [18] T. Denoeux, Calibrated model-based evidential clustering using bootstrapping, *Information Sciences* 528 (2020) 17–45.
- [19] Y. Fan, T. Ma, F. Xiao, An improved approach to generate generalized basic probability assignment based on fuzzy sets in the open world and its application in multi-source information fusion, *Applied Intelligence* (2020) 1–18.
- [20] J. Zhao, Y. Deng, Complex network modeling of evidence theory, *IEEE Transactions on Fuzzy Systems* (2020) 10.1109/TFUZZ.2020.3023760.
- [21] L. Pan, Y. Deng, 202103.00132, *chinaXiv* (2021) 202103.00132.
- [22] D. Dubois, H. Prade, A note on measures of specificity for fuzzy sets, *International Journal of General System* 10 (4) (1985) 279–283.
- [23] U. Hohle, Entropy with respect to plausibility measures, in: *Proc. of 12th IEEE Int. Symp. on Multiple Valued Logic*, Paris, 1982, 1982.
- [24] R. R. Yager, Entropy and specificity in a mathematical theory of evidence, in: *Classic Works of the Dempster-Shafer Theory of Belief Functions*, Springer, 2008, pp. 291–310.
- [25] Y. Deng, Deng entropy, *Chaos, Solitons & Fractals* 91 (2016) 549–553.
- [26] J. Deng, Y. Deng, Information volume of fuzzy membership function, *International Journal of Computers Communications & Control* 16 (1) (2021) 4106. doi:<https://doi.org/10.15837/ijccc.2021.1.4106>.
- [27] Y. Xue, Y. Deng, Tsallis entropy, *Communications in Statistics-Theory and Methods* (2021) 10.1080/03610926.2021.1921804.
- [28] H. Zhang, Y. Deng, Entropy Measure for Orderable Sets, *Information Sciences* 561 (2021) 141–151.
- [29] J. Abellán, Analyzing properties of deng entropy in the theory of evidence, *Chaos Solitons & Fractals* 95 (2017) 195–199.
- [30] Y. Deng, Uncertainty measure in evidence theory, *SCIENCE CHINA Information Sciences* 64 (2021) 10.1007/s11432-020-3006-9.
- [31] F. Liu, X. Gao, J. Zhao, Y. Deng, Generalized belief entropy and its application in identifying conflict evidence, *IEEE Access* 7 (2019) 126625–126633.
- [32] S. Moral-García, J. Abellán, Critique of modified deng entropies under the evidence theory, *Chaos, Solitons & Fractals* 140 (2020) 110112.
- [33] S. Moral-García, J. Abellán, Maximum of entropy for belief intervals under evidence theory, *IEEE Access* 8 (2020) 118017–118029.
- [34] Y. Deng, Information volume of mass function, *International Journal of Computers Communications & Control* 15 (6) (2020) 3983. doi:<https://doi.org/10.15837/ijccc.2020.6.3983>.

- [35] F. Buono, M. Longobardi, A dual measure of uncertainty: The deng entropy, *Entropy* 22 (5). doi:10.3390/e22050582.
URL <https://www.mdpi.com/1099-4300/22/5/582>
- [36] L. Pan, Y. Deng, An association coefficient of a belief function and its application in a target recognition system, *International Journal of Intelligent Systems* 35 (1) (2020) 85-104.
- [37] H. Liao, Z. Ren, R. Fang, A deng-entropy-based evidential reasoning approach for multi-expert multi-criterion decision-making with uncertainty, *International Journal of Computational Intelligence Systems* 13 (2020) 1281-1294. doi:<https://doi.org/10.2991/ijcis.d.200814.001>.
- [38] S. Boulkaboul, D. Djenouri, Dfiot: Data fusion for internet of things, *Journal of Network and Systems Management* doi:10.1007/s10922-020-09519-y.
- [39] M. Zhou, Y.-W. Chen, X.-B. Liu, B.-Y. Cheng, J.-B. Yang, Weight assignment method for multiple attribute decision making with dissimilarity and conflict of belief distributions, *Computers & Industrial Engineering* (2020) 106648.
- [40] M. R. Kazemi, S. Tahmasebi, F. Buono, M. Longobardi, Fractional deng entropy and extropy and some applications, *Entropy* 23 (5). doi:10.3390/e23050623.
URL <https://www.mdpi.com/1099-4300/23/5/623>
- [41] C. E. Shannon, A mathematical theory of communication, *ACM SIG-MOBILE mobile computing and communications review* 5 (1) (2001) 3-55.

Note: Figure translations are in progress. See original paper for figures.

Source: ChinaXiv –Machine translation. Verify with original.