

Evolution of groundwater recharge-discharge balance in the Turpan Basin of China during 1959–2021 (Postprint)

Authors: QIN Guoqiang, WU Bin, DONG Xinguang, DU Mingliang, WANG Bo

Date: 2023-10-17T00:00:00+00:00

Abstract

Groundwater overexploitation is a serious problem in the Turpan Basin, Xinjiang Uygur Autonomous Region of China, causing groundwater level declines and ecological and environmental problems such as the desiccation of karez wells and the shrinkage of lakes. Based on historical groundwater data and field survey data from 1959 to 2021, we comprehensively studied the evolution of groundwater recharge and discharge terms in the Turpan Basin using the groundwater equilibrium method, mathematical statistics, and GIS spatial analysis. The reasons for groundwater overexploitation were also discussed. The results indicated that groundwater recharge increased from $14.58 \times 10^8 \text{ m}^3$ in 1959 to $15.69 \times 10^8 \text{ m}^3$ in 1980, then continued to decrease to $6.77 \times 10^8 \text{ m}^3$ in 2021. Groundwater discharge balance has been broken, the decrease rate of groundwater recharge exceeded that of groundwater discharge during 1980–2021. This research can provide a scientific foundation for the restoration and sustainable use of groundwater in the overexploited areas of the Turpan Basin.

Full Text

Preamble

Journal of Arid Land (2023) 15(9): 1037–1051

<https://doi.org/10.1007/s40333-023-0067-7>

Science Press Springer-Verlag

Evolution of groundwater recharge-discharge balance in the Turpan Basin of China during 1959–2021

QIN Guoqiang, WU Bin*, DONG Xinguang, DU Mingliang, WANG Bo
College of Hydraulic and Civil Engineering, Xinjiang Agricultural University,

Urumqi 830052, China

Abstract: Groundwater overexploitation is a serious problem in the Turpan Basin, Xinjiang Uygur Autonomous Region of China, causing groundwater level declines and ecological and environmental problems such as the desiccation of karez wells and the shrinkage of lakes. Based on historical groundwater data and field survey data from 1959 to 2021, we comprehensively studied the evolution of groundwater recharge and discharge terms in the Turpan Basin using the groundwater equilibrium method, mathematical statistics, and GIS spatial analysis. The reasons for groundwater overexploitation were also discussed. The results indicated that groundwater recharge increased from $14.58 \times 10^8 \text{ m}^3$ in 1959 to $15.69 \times 10^8 \text{ m}^3$ in 1980, then continued to decrease to $6.77 \times 10^8 \text{ m}^3$ in 2021. Groundwater discharge increased from $14.49 \times 10^8 \text{ m}^3$ in 1959 to $16.02 \times 10^8 \text{ m}^3$ in 1989, while continuing to decrease to $9.97 \times 10^8 \text{ m}^3$ in 2021. Since 1980, groundwater recharge-discharge balance has been broken; the decrease rate of groundwater recharge exceeded that of groundwater discharge and groundwater recharge was always lower than groundwater discharge, showing a negative equilibrium, which caused the continuous decrease in groundwater level in the Turpan Basin. From 1980 to 2002, groundwater overexploitation increased rapidly, peaking from 2003 to 2011 with an average overexploitation rate of $4.79 \times 10^8 \text{ m}^3/\text{a}$; then, it slowed slightly from 2012 to 2021, and the cumulative groundwater overexploitation was $99.21 \times 10^8 \text{ m}^3$ during 1980–2021. This research can provide a scientific foundation for the restoration and sustainable use of groundwater in the overexploited areas of the Turpan Basin.

Keywords: groundwater overexploitation; groundwater recharge; groundwater discharge; climate change; human activities; Turpan Basin

Citation: QIN Guoqiang, WU Bin, DONG Xinguang, DU Mingliang, WANG Bo. 2023. Evolution of groundwater recharge-discharge balance in the Turpan Basin of China during 1959–2021. *Journal of Arid Land*, 15(9): 1037–1051. <https://doi.org/10.1007/s40333-023-0067-7>

1 Introduction

Groundwater is not only an important component of water resources, but also plays a vital role in resource security [?], ecological maintenance [?], and geological security [?, ?]. Climate change and human activities have caused changes in groundwater resources in some regions in recent years, including serious problems such as overexploitation and pollution [?, ?, ?], which affect regional water security [?], ecological security [?, ?], and geological security [?]. Therefore, determining the evolution of groundwater resources is necessary to promote the management and protection of groundwater resources and ensure water, ecological, and geological safety. Because of the importance of groundwater resources, theoretical and practical research has been conducted, especially in light of current problems such as increasingly significant climate change [?, ?], intense hu-

man activities [?], and their effects, e.g., rapid land use changes [?, ?, ?]. These problems have an important impact on the dynamic balance and recharge mechanism of groundwater, bringing the evolution of groundwater recharge to the forefront of scientific research [?, ?, ?].

The evolution of groundwater has been studied in depth [?, ?]. Both precipitation and exploitation impact the evolution of groundwater flow field, although exploitation has a stronger impact than precipitation [?]. The groundwater drawdown funnel's growth rate accelerates as groundwater extraction increases. Groundwater level in the funnel tends to stabilize or rise as groundwater extraction stabilizes or declines [?]. Wu et al. [?] pointed out that human activities are the key factor influencing the evolution of groundwater recharge; nevertheless, the impact of climate change can be negligible.

The development of an agro-ecosystem is directly related to changes in groundwater storage and water quality over time [?]. The primary cause of regional groundwater level decline is agricultural irrigation, and groundwater level decline can be effectively avoided by reducing agricultural water use [?]. Although previous research has conducted in-depth analysis on one or several characteristic elements of groundwater in a certain area, there are few studies on the long-term, multi-element quantitative analysis of the evolution of groundwater recharge-discharge balance.

Turpan Basin is the first groundwater overexploited region identified in Xinjiang Uygur Autonomous Region of China and remains in overexploitation today. Continuous high intensity exploitation of groundwater is the main reason for groundwater overexploitation, according to qualitative and semi-quantitative research on the sustainable exploitation of groundwater resources in the Turpan Basin [?, ?, ?], as well as the influencing factors of the dynamic characteristics of groundwater level [?, ?]. At present, there are no objective and comprehensive reports on the evolution of groundwater in the Turpan Basin based on quantitative data. Specifically, this study investigated the evolution of seven groundwater recharge terms and six groundwater discharge terms to explore the recharge-discharge balance and its influencing factors, and revealed the causes of groundwater overexploitation in the Turpan Basin. This study can provide scientific basis for the sustainable development and utilization management of groundwater overexploited areas in the Turpan Basin.

2.1 Study Area

The Turpan Basin is located in the eastern part of Xinjiang Uygur Autonomous Region, China, at longitude of 87°06–91°55 E and latitude of 41°12–43°40 N. The administrative area includes the Gaochang District of Turpan City, Shanshan County, and Toksun County (Fig. 1 [Figure 1: see original paper]). The Turpan Basin is a fully enclosed basin; it is surrounded by mountains to the north, west, and south, and is separated from the Hami Basin by hills to the east. The Yanshan and Huoyanshan mountains cross the centre of the basin

from west to east, dividing the plain area into two sub-basins: the north basin and the south basin. At the centre of the Turpan Basin is the Aiding Lake, with a lake surface elevation of -154 m; it marks the lowest inland point in China. This study covers the Turpan Basin's artificial oasis plain region, including 4921.52 km² area in the north basin and 5954.79 km² area in the south basin.

Because of its unique geographical location and topography, the Turpan Basin has a warm arid climate typical of temperate continental deserts, with high temperatures and little precipitation. The annual average temperature at the centre of the basin is 14.00°C and the average annual precipitation is 16.40 mm. The water system of the Turpan Basin originates from the middle and high mountains in the west and north. The water recharge sources are ice and snow meltwater and mountain precipitation; surface runoff flows from the mountains to the plain area and finally into the Aiding Lake located at the centre of the basin. Fourteen large and small rivers are developed in the basin, with an average annual runoff of 8.95×10^8 m³ [?]. Among them, nine rivers with an average annual runoff of 6.74×10^8 m³ belong to the Bogda Mountains system, three rivers with an average annual runoff of 2.00×10^8 m³ belong to the Tengger Mountains system, and two rivers with an average annual runoff of 0.21×10^8 m³ belong to the Jorotag Mountains system.

The thickness of the unconsolidated Fourth Series rocks in the Turpan Basin is 150 – 400 m, and the thickness of the Fourth Series in the local section west of Toksun County exceeds 500 m; thus, they provide sufficient storage space for groundwater. The north basin is a gravelly plain with a single diving aquifer structure, and the lithology of the aquifer is mainly pebbles and gravel. In the southern part of Shenjin and Qiktai townships in Shanshan County, a fine soil plain appears with double and multilayered structures, consisting of diving and pressurised aquifers; the lithology of the aquifer is mainly medium and coarse sands and gravels. The south basin is surrounded by a gravelly plain with a single submerged aquifer structure, and the central part of this basin is a fine soil plain with double and multilayered structures, consisting of submerged and confined aquifers; the lithology of the aquifer is mainly medium and fine sands and silt. The direction of groundwater runoff generally follows the topographic slope, from north to south in the north basin and from the surrounding area to the Aiding Lake in the south basin. Most of groundwater in the Turpan Basin is connected hydraulically through three gullies cutting the Huoyanshan Mountain, and the lateral outflow in the north basin is part of the lateral recharge in the south basin. The intra-annual and inter-annual dynamics of groundwater level in the basin are typical of artificial exploitation, and the inter-annual dynamics have been declining continuously since 1980, when the cumulative decline exceeded 50.0 m in some areas.

2.2 Data Sources

Groundwater recharge in the plain area of the Turpan Basin includes the mountain front's lateral infiltration recharge (QMFLIR; 10^8 m³/a), latent river flow recharge (QLRFR; 10^8 m³/a), river infiltration recharge (QRIR; 10^8 m³/a), canal leakage recharge (QCLR; 10^8 m³/a), reservoir and pond seepage recharge (QRPSR; 10^8 m³/a), and field infiltration recharge (QFIR; 10^8 m³/a). The recharge terms of groundwater transformation (QRETURN; 10^8 m³/a) include mechanical well extraction (QMW; 10^8 m³/a), karez well outflow (QK; 10^8 m³/a), spring overflow (QS; 10^8 m³/a), and artesian well outflow (QAW; 10^8 m³/a). Because very few regions in the plain area of the Turpan Basin receive more than 10.00 mm of precipitation annually, the precipitation infiltration recharge can be ignored. QK, QS, river discharge (QR; 10^8 m³/a), QAW, QMW, and evapotranspiration (QE; 10^8 m³/a) are the principal groundwater discharge terms in the Turpan Basin.

All groundwater-related data for the Turpan Basin since 1959 were comprehensively analyzed in this study. These results can be divided into five periods on a time scale. First, the "Report on Hydrogeological Conditions and Water Resources Development and Utilization in the Turpan Basin" was completed by the First Brigade of Hydrogeology, Xinjiang Bureau Geo-exploration & Mineral Development in 1963 [?]; its status quo year is 1959. Second, results during this period were from the "Comprehensive Assessment of Turpan Basin Water Resources 1/200,000" [?] and the "Research Report on the Efficient Use and Development of Groundwater in the Turpan Basin" [?], and the status quo year is 1989. Third, the "Research Report on Sustainable Utilization of Groundwater Resources in the Turpan Basin" [?] (current year of 2003) was completed in 2005 by the Japan International Industry Corporation. Fourth, the "Report on Groundwater Exploration in the Turpan Basin" was completed in 2013 by the First Brigade of Hydrogeology, Xinjiang Bureau Geo-exploration & Mineral Development [?], and the status quo year is 2011. Fifth, the status quo year of this study (Qin et al., 2021) is 2021, and the survey was conducted in June 2021. This research quantitatively examined groundwater recharge and discharge terms as well as the dynamics of groundwater recharge-discharge balance in the Turpan Basin during 1959–2021 using the data obtained in the above mentioned five periods.

The Turpan Prefecture Bureau of Hydrology and Water Resources constructed 37 monitoring wells in 1985 to form a groundwater monitoring system in the Turpan Basin. In 2017, 33 new groundwater level monitoring wells under state control were installed. This study extensively used the long-term groundwater level monitoring data from all 70 monitoring wells to validate the calculation data of groundwater overexploitation. Furthermore, the formulas used in the calculation process were taken from Zhou et al. [?], and the parameters were primarily based on the findings of this research experiment or referred to the study of Dong and Deng [?], as well as the survey data obtained in June 2021.

2.3.1 Methods for Processing Series Data

We analyzed the groundwater recharge and discharge information derived from the groundwater balance information in the five periods. The evolution of groundwater recharge and discharge terms and recharge-discharge balance was mainly studied using mathematical statistics and GIS spatial analysis. The baseline year was 1959, with 1989, 2003, 2011, and 2021 as the reference years. The data before 2021 were directly referred to the previous research results. The groundwater balance method was mostly employed to process the survey data in 2021, and the following data calculation methods were also used. We further used Excel 2016 to perform the analysis and ArcGIS 10.2 to draw the figures.

2.3.2 Calculation of the Survey Data

(1) Groundwater recharge calculation

QMFLIR and QLRFR were calculated using the Darcy formula:

$$QMFLIR/LRFR = 365 \times K \times I \times M \times L \times \sin(a)$$

where QMFLIR/LRFR represents the QMFLIR or QLRFR ($10^8 \text{ m}^3/\text{a}$); K is the aquifer permeability coefficient (m/d); I is the groundwater hydraulic gradient (%); M is the average thickness of the aquifer at the calculated section (m); L is the length of the calculated section (m); and a is the angle between the calculated section and the groundwater flow direction ($^\circ$).

QRIR was determined as:

$$QRIR = Q_{\text{up}} - Q_{\text{sink}} - Q_{\text{divert}} - Q_{\text{evaporation}} - Q_{\text{eiz}}$$

where Q_{up} is the measured runoff volume at the upstream hydrographic section of the river ($10^8 \text{ m}^3/\text{a}$); Q_{sink} is the volume of water that enters the river ($10^8 \text{ m}^3/\text{a}$); Q_{divert} is the volume of water diverted from the irrigated area between the upstream and downstream hydrographical sections of the river ($10^8 \text{ m}^3/\text{a}$); $Q_{\text{evaporation}}$ is the evaporation from the river surface between the upstream and downstream hydrographical sections of the river ($10^8 \text{ m}^3/\text{a}$); and Q_{eiz} is the evaporation from the infiltration zone between the upstream and downstream hydrographical sections of the river on both sides of the river channel ($10^8 \text{ m}^3/\text{a}$). It should be noted that Q_{eiz} was negligible in the Turpan Basin, because most river channels are wide and shallow.

QCLR was calculated as:

$$QCLR = Q_{\text{diversion1}} \times \gamma' \times \gamma'' \times (1 - \eta)$$

where $Q_{\text{diversion1}}$ is the average multiyear diversion of the canal system ($10^8 \text{ m}^3/\text{a}$); γ is the canal leakage correction coefficient; γ is the canal impermeability correction coefficient; and β is the effective utilization coefficient of the canal system.

QFIR was calculated as:

$$Q_{\text{FIR}} = Q_{\text{diversion2}} \times \beta$$

where $Q_{\text{diversion2}}$ is the field irrigation diversion ($10^8 \text{ m}^3/\text{a}$); and β is the field infiltration recharge coefficient.

QRPSR was determined as:

$$Q_{\text{RPSR}} = Q_{\text{vrp}} \times a_1$$

where Q_{vrp} is the volume of the reservoir and pond ($10^8 \text{ m}^3/\text{a}$); and a_1 is the seepage recharge coefficient of the reservoir and pond.

The calculation of QRETURN was similar to that of QFIR. First, the agricultural irrigation wells, karez wells, springs, and artesian wells in use were counted, and the infiltration recharge coefficient was selected on the basis of the buried groundwater level in the irrigated area. Next, the infiltration recharge of groundwater for irrigation was calculated in the field, as follows:

$$Q_{\text{RETURN}} = Q_{\text{SGW}} \times a_2$$

where Q_{SGW} is the sum of the groundwater used by mechanical wells, karez wells, springs, and artesian wells ($10^8 \text{ m}^3/\text{a}$); and a_2 is the groundwater return infiltration coefficient, which has an empirical value depending on the study area.

(2) Groundwater discharge calculation

The amounts of QK, QS, QAW, QMW, and QR were based on the survey data obtained in June 2021. QE was classified into irrigated groundwater evapotranspiration excretion (Q_{Ecg} ; $10^8 \text{ m}^3/\text{a}$) and non-irrigated groundwater evapotranspiration excretion (Q_{Eng} ; $10^8 \text{ m}^3/\text{a}$).

Q_{Ecg} was calculated as:

$$Q_{\text{Ecg}} = E_{601} \times C \times F \times C' \times E_{601.1}$$

where E_{601} is the annual water surface evaporation (mm); C is the groundwater evaporation coefficient; F is the area of the calculation region (km^2); C' is a correction coefficient, depending on the evaporation from vegetation under crop cover conditions (the cover rate was taken as 90%); and $E_{601.1}$ is the water

surface evaporation during crop growth and maturation period from April to September (mm).

QEng was determined as:

$$Q_{Eng} = E_{601} \times C \times F \times C''$$

where C is a correction coefficient for evaporation from vegetation under vegetation cover conditions.

(3) Calculation of cumulative groundwater storage variables

The following equation was used to determine cumulative groundwater storage variables (ΔW ; $10^8 \text{ m}^3/\text{a}$):

$$\Delta W = \mu \times \frac{h_1 - h_2}{\Delta t} \times A$$

where μ is the aquifer feeding degree in the groundwater change zone of the calculation area; h_1 is the groundwater level at the beginning of the calculation period (m); h_2 is the groundwater level at the end of the calculation period (m); A is the area of the groundwater level variation zone (km^2); and Δt is the groundwater equilibrium calculation period (a).

3.1 Evolution of Groundwater Recharge

Groundwater recharge in the Turpan Basin from 1959 to 2021 is shown in Figure 2 [Figure 2: see original paper] and Table 1. The mode, process, and intensity of groundwater recharge changed significantly; primarily, surface water conversion recharge altered significantly, whereas natural recharge did not change significantly.

QMFLIR was approximately $1.60 \times 10^8 \text{ m}^3/\text{a}$, which essentially remained unchanged, owing to consistent precipitation and river runoff in recent years with a minor rising tendency. Natural QLRFR was $0.69 \times 10^8 \text{ m}^3/\text{a}$. Specifically, before 1980, development was slow and few reservoirs were built. However, after 1980, with the acceleration of reform, 12 mountain reservoirs were built in the basin, such as Ertanggou, Kekeya, and Kanerqi. Because the impermeability of the dam base essentially cut off the submerged river flow, only a few smaller river gullies without mountain barrage reservoirs remained to be recharged by submerged river flow, which exhibited a slow decrease in QLRFR from 1959 to 1989 and a rapid decline in QLRFR from 1989 to 2021.

QRIR is affected by both river runoff and canal diversion. According to the hydrological data provided by the Turpan Prefecture Bureau of Hydrology and Water Resources, the runoff volume of the rivers in the basin was essentially stable during 1959–2021. However, since the 1990s, control reservoirs and barrage headworks have been built to regulate surface water, changing the process and

volume of river runoff. Consequently, supporting channel diversions increased and river overflow decreased. QRIR showed a pattern consistent with QLRFR: a slow decrease from 1959 to 1989 and a rapid decrease from 1989 to 2021.

Changes in the seepage recharge of the canal system are related mainly to the amount of diversion and canal impermeability. Since 1960, diversion trunk and branch canals have been under construction in the basin, and the diversion volume has increased continuously. In 1980, the construction of canals was shifted to increase the lining rate simultaneously. Therefore, QCLR showed a slow increase from 1959 to 1989, followed by a rapid decrease from 1989 to 2021.

The variation in QFIR is related mainly to the amount of field diversion, irrigation methods, and the depth of groundwater level in the irrigated area. The amount of QFIR increased continuously before 1990, and then essentially stable. Before 1980, most of the basin was irrigated with large amounts of water. In 2000, the conventional field water-saving irrigation methods, such as border irrigation and fine-flow furrow irrigation, were popularized in the basin. After 2005, advanced drip irrigation and other advanced water-saving technologies started to be introduced and promoted. The depth of groundwater level in the irrigated area of the basin remained stable until 1980 and declined continuously thereafter. Generally speaking, QFIR increased from 1959 to 1989 while decreased from 1989 to 2021.

QRPSR includes the seepage recharge of water reservoirs and ponds in the plain area. Before 2011, with increasing water diversion, several water reservoirs and ponds were built in the basin, resulting in the increase of infiltration. After 2011, the seepage gradually decreased with the completion of de-risking and the development of various water storage projects. Therefore, QRPSR increased from 1959 to 2011, then decreased until 2021.

QRETURN was $5.70 \times 10^8 \text{ m}^3$ in 1959, increased to $6.40 \times 10^8 \text{ m}^3$ in 1980, and remained nearly constant from 1980 to 1990. Then, QRETURN decreased rapidly from 1990 to 2021, at a value of $1.48 \times 10^8 \text{ m}^3$ in 2021. The main reason is the rapid decrease in groundwater outflow, which caused the canal and field water utilization coefficients to increase gradually and the depth of groundwater level to decrease.

3.2 Evolution of Groundwater Discharge

Results of groundwater discharge terms in the Turpan Basin from 1959 to 2021 are shown in Table 1. During 1959–2021, groundwater outflow in the Turpan Basin showed a significant change due to the decline in groundwater level.

We analyzed the number of karez wells and QK for nine periods: 1959, 1959, 1987, 1990, 1994, 2004, 2011, 2014, and 2021 (Fig. 3 [Figure 3: see original paper]). From 1959 to 1987, the number of karez wells and the value of QK decreased slowly first and then decreased more rapidly before exhibiting a slow decrease. During 1957–1987, the number of karez wells decreased at an average

rate of 10 bars/a, and QK decreased at a rate of $0.06 \times 10^8 \text{ m}^3/\text{a}$. From 1987 to 2011, the number of karez wells decreased most rapidly, with an average rate of 30 bars/a, and QK decreased at a rate of $0.12 \times 10^8 \text{ m}^3/\text{a}$. From 2011 to 2021, the decreasing rate of the number of karez wells slowed gradually, with an average rate of 7 bars/a, and QK decreased at a rate of $0.05 \times 10^8 \text{ m}^3/\text{a}$. It is known from the principle of karez wells [?] that the continuous decline in groundwater level is the leading cause of the drying up and flow decay of karez wells.

The available information shows that the mechanical wells in the Turpan Basin were primarily established in 1960. QMW in the Turpan Basin exhibited distinct behaviours in different periods (Fig. 4 [Figure 4: see original paper]). First, slow growth in QMW occurred from 1960 to 1980. In 1960, the Turpan Basin had 16 mechanical wells, with a total QMW value of $0.01 \times 10^8 \text{ m}^3$. By 1980, 1058 mechanical wells existed, with a total QMW value of $1.82 \times 10^8 \text{ m}^3$, an average annual increase number of 52 new mechanical wells, and an increase rate in QMW of $0.09 \times 10^8 \text{ m}^3/\text{a}$. Second, a rapid growth in QMW occurred from 1980 to 1990, which coincides with the reform policy and land development. The number of mechanical wells increased, at an average annual increase number of 133 new mechanical wells and an increase rate in QMW of $0.31 \times 10^8 \text{ m}^3/\text{a}$. Third, from 1990 to 2003, the increase rate of QMW decreased, with 81 new mechanical wells added each year. During this period, QMW increased by $0.12 \times 10^8 \text{ m}^3/\text{a}$. Fourth, from 2003 to 2010, the number of new mechanical wells increased rapidly, with an average of 334 new mechanical wells added each year. QMW during this period increased by $0.31 \times 10^8 \text{ m}^3/\text{a}$, reaching a peak of $8.60 \times 10^8 \text{ m}^3$ in 2010. Fifth, in 2006, the Turpan Basin was designated as a groundwater overexploited area, and from 2010 to 2021, a series of groundwater control measures were introduced, beginning to limit the amount of QMW, shutting down some mechanical wells, and scrapping an average of 57 mechanical wells every year. Therefore, QMW during this period decreased at an average of $0.19 \times 10^8 \text{ m}^3/\text{a}$, reaching up to $6.71 \times 10^8 \text{ m}^3$ by 2021 (Fig. 4 [Figure 4: see original paper]).

Artesian wells appear mainly in the south basin and the area north of the Huoyanshan Mountain. The number of artesian wells increased with the increase of mechanical wells. QAW also increased from 1970 to 1980 and remained stable at an average annual value of $0.47 \times 10^8 \text{ m}^3$ during 1980–1989 (Fig. 5 [Figure 5: see original paper]). After 1989, the number of mechanical wells continued to increase, and groundwater pressure in artesian wells decreased. Correspondingly, QAW also decreased continuously. No self-flowing behaviour was observed in artesian wells until the survey in June 2021.

Spring water in the Turpan Basin is concentrated mainly in the area north of the Huoyanshan Mountain. QS decreased very little between 1960 and 1989, and the decay rate of QS increased after 1989, with an average annual decay rate of $0.05 \times 10^8 \text{ m}^3$ from 1990 to 2011 (Fig. 5 [Figure 5: see original paper]). Further, from 2011 to 2021, the average annual decay rate of QS

increased to $0.07 \times 10^8 \text{ m}^3$. The continuous decrease in QS since 1989 was mainly caused by the continuous decline in groundwater level in the north of the Huoyanshan Mountain.

As shown in Figure 5 [Figure 5: see original paper], QR was essentially stable before 1980, at approximately $0.70 \times 10^8 \text{ m}^3/\text{a}$, and decreased continuously after 1980. This phenomenon was not observed until the survey in June 2021, mainly because of the continuous decline in groundwater level. QE discharge is closely related to groundwater level and vegetation cover. It remained essentially stable from 1959 to 1980; after 1980, however, it decreased continuously, until 2021. The main reason is the continuous decline of groundwater level in areas above 6.0 m (the limit of groundwater evaporation and transpiration).

3.3 Evolution of Groundwater Recharge-Discharge Balance

The evolution of groundwater recharge-discharge balance in the Turpan Basin since 1959 was obtained by summarizing various groundwater recharge and discharge terms, as shown in Figure 6 [Figure 6: see original paper]. From 1959 to 1980, both groundwater recharge and discharge in the Turpan Basin showed a slightly increasing trend and remained essentially in equilibrium. Since groundwater recharge-discharge balance was disrupted in 1980, the amount of discharge was always greater than that of recharge, indicating a negative equilibrium. From 1980 to 2021, the rate of groundwater overexploitation in the basin increased rapidly and then decreased slightly. Groundwater overexploitation rate was highest from 2003 to 2011, reaching $4.79 \times 10^8 \text{ m}^3/\text{a}$, after which it began to decrease, consistent with the groundwater overexploitation zone management conducted after 2010 and the reduction in groundwater extraction. The cumulative groundwater overexploitation in the Turpan Basin from 1980 to 2021 was calculated to be $99.21 \times 10^8 \text{ m}^3$, as shown in Table 2 .

In addition, Figure 6 [Figure 6: see original paper] shows that groundwater recharge and discharge in the Turpan Basin indicated a continuous decrease after 1980. Groundwater recharge decreased from $15.69 \times 10^8 \text{ m}^3$ in 1980 to $6.77 \times 10^8 \text{ m}^3$ in 2021, a decrease of 56.85% (average decrease rate of $0.22 \times 10^8 \text{ m}^3/\text{a}$). Groundwater discharge decreased from $15.66 \times 10^8 \text{ m}^3$ in 1980 to $9.97 \times 10^8 \text{ m}^3$ in 2021, a decrease of 36.33% (average decrease rate of $0.14 \times 10^8 \text{ m}^3/\text{a}$). The rate of decrease in recharge was always greater than the rate of decrease in discharge, and the recharge volume was always lower than the discharge volume, indicating a negative equilibrium. This is the result of the continuous decline of groundwater level, and also the real objective cause of groundwater overexploitation in the Turpan Basin.

4.1 Verification of Groundwater Overexploitation

Groundwater level in the Turpan Basin has been declining continuously since 1980. The decline can be divided into four stages on the basis of groundwater recharge-discharge balance shown in the previous sections and groundwater level

monitoring data. Figure 7 [Figure 7: see original paper] shows the spatial distribution of groundwater level decline in each stage, and the details are described and analyzed as follows.

- (1) During 1980–1989, the south basin showed a slow decline in groundwater level, mainly in Tuyuk, Darank, and Lukqin townships in Shanshan County, located in the south of the Huoyanshan Mountain. Because these areas took the lead in reclaiming wasteland and drilling wells, groundwater discharge in these areas is greater than groundwater recharge. Groundwater level in the whole basin first began to decline at rates varying from 0.1 to 0.4 m/a. As the areas of decline in groundwater level expanded, the annual decline rate gradually increased. For example, groundwater level in the irrigated area of the whole basin decreased at an average rate of 0.1 m/a.
- (2) During the rapid decline phase from 1989 to 2003, the decline rate of groundwater level increased in most areas of the south basin, and the areas of decline in groundwater level extended from the region around Tuyuk Township of Shanshan County in the south of the Huoyanshan Mountain to the entire oasis plain in the south of Shanshan County. A groundwater level landing funnel was formed, with an overall average decline rate of 0.4 m/a, and the decline rate at the centre of the funnel has reached up to 2.7 m/a.
- (3) During 2003–2011, the decline in groundwater level slowed in the north basin; by contrast, the entire south basin underwent rapid decline in groundwater level, showing an increase in the decline rate of groundwater level. The areas of decline in groundwater level extended from Shanshan County in the southern part of the Huoyanshan Mountain to the other areas in the south of the mountain, and from the east of the Yanshan Mountain to the western edge of the Kumtag Desert. The region also extended to the north of the Huoyanshan Mountain, i.e., in the areas from Qiktai Township to Shenjin Township in Shanshan County and the areas of Bostan, Yilahu, and Guolebuy townships in Toksun County. The average decline rate of groundwater level in the oasis plain was 1.1 m/a, and the decrease rate in Tuyuke Town was the highest (3.2 m/a), with a cumulative decline of 24.0 m.
- (4) During 2011–2021, the basin-scale decline rate of groundwater level gradually decreased, and Turpan City began to control its groundwater over-exploitation by reducing water use, sealing or filling mechanical wells, and reducing groundwater extraction. The trend of continuous decline in groundwater level in the periphery of the irrigated area near the mountain front was alleviated; however, the area with high-intensity mechanical well extraction of groundwater in the centre of the irrigated area still declined rapidly. Groundwater level in the basin-scale oasis plain area declined at an average rate of 1.0 m/a, and the rate of decline in the overexploited area of the south basin was even higher, averaging 1.2 m/a.

The cumulative groundwater storage during 1980–2021 was $102.10 \times 10^8 \text{ m}^3$. Table 3 displays the computation results of groundwater storage variables for each time period. Annual groundwater storage variables gradually increased from 1980 to 2011, then they began to decline from 2011 to 2021. The previous section calculated the cumulative groundwater overexploitation ($99.21 \times 10^8 \text{ m}^3$) during 1980–2021 through the balance of groundwater recharge and discharge, which is consistent with the cumulative groundwater storage variables (difference of 2.9%), so the calculated groundwater overexploitation in the Turpan Basin during 1980–2021 is relatively accurate and reliable.

4.2 Primary Causes of Groundwater Recharge and Discharge Evolution

Climate change and human activities are primarily driving the evolution of groundwater recharge-discharge balance. There has been a warming trend in the Turpan Basin since 1950, with an average temperature rise rate of $0.45^\circ\text{C}/\text{decade}$ [?, ?, ?]. Precipitation also showed a moderate rising tendency during 1959–2021, with an increase rate of approximately $1.61 \text{ mm}/\text{decade}$ [?, ?, ?]. River runoff in the Turpan Basin was steady during 1959–2021, with a slightly increasing trend [?, ?, ?]. Precipitation and evaporation had little impact on groundwater level in arid areas [?, ?, ?], while human activities were the dominant factor influencing groundwater level.

The proportion of agricultural water use in the Turpan Basin was as high as 92.21%, and the continuous decline in groundwater level was caused by the expansion of the irrigated area and the advancement of irrigation methods, not by climate change or the single reason of increased groundwater extraction by mechanical wells. The river bed of the mountain reservoirs was blocked off, lowering the amount of latent river flow. Furthermore, as a result of water conservation initiatives, water flowed through channels instead of rivers, reducing river leakage. The seepage prevention rate of the canal system rose despite the increased canal water diversion, but the canal leakage dropped. Additionally, the seepage prevention rate of reservoirs and ponds was improved, and the seepage amount from reservoirs and ponds decreased. Finally, the area of cultivated land was expanded, effective water-saving technology was promoted, irrigation quota and the amount of field infiltration water were significantly decreased, and the amount of return water infiltration from mechanical wells, springs, and karez wells were also significantly reduced.

This finding contradicts the prior understanding that over-extraction of groundwater from wells, which was only quantitatively examined as one element in groundwater extraction from wells in terms of discharge volume, is the primary cause of overexploitation. This study was more objective, comprehensive, and scientific as it systematically analyzed seven groundwater recharge terms and six groundwater discharge terms. Currently, the penetration rate of efficient water-saving has reached up to 90% in the Turpan Basin. The water-saving opportu-

nity is not obvious, and the existing water resources are unable to support the current irrigated area. To achieve balanced groundwater recharge and discharge, it is, therefore, necessary to significantly decrease the irrigated area or carry out industrial transformation, and reduce water consumption and the quantity of groundwater exploitation without resorting to external water sources. Then, the decline in groundwater level can be reversed.

5 Conclusions

In this study, the evolution of seven groundwater recharge terms and six discharge groundwater terms from 1959 to 2021 was used to analyze groundwater recharge-discharge balance in several historical periods (1959, 1970, 1980, 1989, 2003, 2011, and 2021), and the reasons for the continuous overexploitation of groundwater were revealed. Additionally, we determined the extent of groundwater overexploitation and reached the following conclusions.

- (1) From 1959 to 2021, groundwater recharge first increased slightly and then decreased continuously. The total groundwater recharge increased from $14.58 \times 10^8 \text{ m}^3$ in 1959 to $15.69 \times 10^8 \text{ m}^3$ in 1980 and then decreased to $6.77 \times 10^8 \text{ m}^3$ by 2021.
- (2) From 1959 to 2021, groundwater discharge showed a slight increase followed by a continuous decrease, increasing from $14.49 \times 10^8 \text{ m}^3$ in 1959 to $16.02 \times 10^8 \text{ m}^3$ in 1989 and then decreasing continuously to $9.97 \times 10^8 \text{ m}^3$ in 2021.
- (3) Groundwater recharge and discharge in the Turpan Basin were in equilibrium before 1980. Subsequently, from 1980 to 2021, groundwater recharge decreased by 56.85%, with an average decrease rate of $0.22 \times 10^8 \text{ m}^3/\text{a}$, and groundwater discharge decreased by 36.33%, with an average decrease rate of $0.14 \times 10^8 \text{ m}^3/\text{a}$. The rate of decrease in groundwater recharge was always greater than the rate of decrease in groundwater discharge, and the amount of groundwater recharge was always lower than the amount of groundwater discharge. This is the real objective cause of groundwater overexploitation in the Turpan Basin.
- (4) From 1980 to 2021, groundwater storage decreased, and the decay rate initially accelerated and then decelerated, leading to a total overexploitation of $99.21 \times 10^8 \text{ m}^3$.

The evolution of groundwater recharge-discharge balance in the Turpan Basin is explored in detail in this study, and our understanding of groundwater overexploitation is expanded. However, further improvement is required, and the impact of land and water resources utilization on groundwater should be considered in the future.

Conflict of interest: The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Acknowledgments: This research was supported by the Natural Science Foundation of Xinjiang Uygur Autonomous Region, China (2021D01A99) and the National Natural Science Foundation of China (51969029). The authors express appreciation for the reviewers and editors, who helped improve the quality of this paper.

Author Contributions: Conceptualization: QIN Guoqiang, WU Bin, DONG Xinguang; Data curation: QIN Guoqiang, DU Minliang, WANG Bo; Methodology: QIN Guoqiang, WU Bin; Formal analysis: QIN Guoqiang, DU Minliang; Writing - original draft preparation: QIN Guoqiang, WU Bin, DONG Xinguang, DU Minliang, WANG Bo; Writing - review and editing: QIN Guoqiang, WU Bin, DONG Xinguang; Funding acquisition: WU Bin, DONG Xinguang; Resources: QIN Guoqiang, WU Bin; Supervision: WU Bin, DONG Xinguang.

References

- Abdisalam J, Shi Y H. 2015. Research on the groundwater resources condition at Turpan Region. *China Rural Water and Hydropower*, (11): 55–58, 64. (in Chinese)
- Adhikari R K, Yilmaz A G, Mainali B, et al. 2022. Methods of groundwater recharge estimation under climate change: A review. *Sustainability*, 14(23): 15619, doi: 10.3390/su142315619.
- Alanur A, Tursun K, Mahpirat N, et al. 2019. A comparison on characteristics of temperature and precipitation in Turpan City and Hami City. *Journal of Northwest Normal University (Natural Science)*, 55(3): 105–111, 134. (in Chinese)
- Amini A, Hesami A. 2017. The role of land use change on the sustainability of groundwater resources in the eastern plains of Kurdistan, Iran. *Environmental Monitoring and Assessment*, 189: 297, doi: 10.1007/s10661-017-6014-3.
- Cha J, Lee J Y, Chia R W. 2023. Microplastics contamination and characteristics of agricultural groundwater in Haeon Basin of Korea. *Science of The Total Environment*, 864: 161027, doi: 10.1016/j.scitotenv.2022.161027.
- Chen F, Ding Y Y, Li Y Y, et al. 2020a. Practice and consideration of groundwater overdraft management in North China. *South to North Water Transfers and Water Science & Technology*, 18(2): 191–198. (in Chinese)
- Chen F, Xu X Y, Yang Y, et al. 2020b. Analysis of evolutionary trends and influencing factors of groundwater resources in China. *Advance in Water Science*, 31(6): 811–819. (in Chinese)
- Chen H R, Wu M S, Duan Z, et al. 2023. Forecasting the human and climate impacts on groundwater resources in the irrigated agricultural region of North China Plain. *Hydrological Processes*, 37(3): e14853, doi: 10.1002/hyp.14853.

- Chen L. 2014. The study of regional hydrogeological conditions and groundwater circulation in Turpan Basin. PhD Dissertation. Beijing: China University of Geosciences. (in Chinese)
- Chen Q. 1998. Annual and flood season variation characteristics of surface runoff in northern mountainous area of Turpan Basin. *Bimonthly of Xinjiang Meteorology*, (5): 36–39. (in Chinese)
- Cui H, Wang R, Zhang M Y, et al. 1990. Research Report on Groundwater Resources and Rational Development and Utilization in the Turpan Basin. Urumqi: The First Brigade of Hydrogeology, Xinjiang Bureau Geo-exploration & Mineral Development, 76–77. (in Chinese)
- Deng M J. 2010. Kariz wells in arid land and mountain-front depressed ground reservoir. *Advances in Water Science*, 21(6): 748–756. (in Chinese)
- Dong X G, Deng M J. 2005. *Groundwater Resources in Xinjiang*. Urumqi: Xinjiang Science and Technology Press, 92–106. (in Chinese)
- Duque C, Rosenberry D O. 2022. Advances in the study and understanding of groundwater discharge to surface water. *Water*, 14(11): 1698, doi: 10.3390/w14111698.
- Feng H M, Zhang G H, Wang D L. 2014. Analysis of the driving forces of groundwater flow field evolution in Shijiazhuang area in the past 50 years. *Journal of Hydraulic Engineering*, 45(2): 180–186. (in Chinese)
- Huang D Q, Cui J, Li C Z. 1990. Report on the Comprehensive Evaluation of Water Resources in the Turpan Basin, Xinjiang 1/200,000. Urumqi: The First Brigade of Hydrogeology, Xinjiang Bureau Geo-exploration & Mineral Development, 77–79. (in Chinese)
- Keranmu A, Abudushalike N. 2014. Analysis of temperature and rainfall changes in recent 52 years in Turpan city, Xinjiang. *Journal of Arid Land Resources and Environment*, 28(12): 45–50. (in Chinese)
- Kronvang B, Wendland F, Kovar K. 2020. Land use and water quality. *Water*, 12(9): 2412, doi: 10.3390/w12092412.
- Le Brocque A F, Kath J, Reardon-Smith K. 2018. Chronic groundwater decline: A multi-decadal analysis of groundwater trends under extreme climate cycles. *Journal of Hydrology*, 561: 976–986.
- Li F L, Chen H W, Wang K R, et al. 2018. A review of research on groundwater-supported ecosystems. *Advance in Water Science*, 29(5): 750–758. (in Chinese)
- Li J, Zhou Y X, Wang W K, et al. 2022a. Response of hydrogeological processes in a regional groundwater system to environmental changes: A modeling study of Yinchuan Basin, China. *Journal of Hydrology*, 615: 128619, doi: 10.1016/j.jhydrol.2022.128619.

- Li Y F, Wang H L, Sun B. 1963. Hydrogeological Conditions and Water Resources Development and Utilization in the Turpan Basin, Xinjiang. Urumqi: The First Brigade of Hydrogeology, Xinjiang Bureau Geo-exploration & Mineral Development, 41–43. (in Chinese)
- Li Y T, Friedman N, Teatini P, et al. 2022b. Sensitivity analysis of factors controlling earth fissures due to excessive groundwater pumping. *Stochastic Environmental Research and Risk Assessment*, 36(11): 3911–3928.
- Li Y Y, Cao J T, Shen F X. 2014. Changes in renewable water resources in China from 1956 to 2010. *Scientia Sinica (Terrae)*, 44(9): 2030–2038. (in Chinese)
- Ma J Z, Li J J, Gao Q Z. 2002. Groundwater evolution and its influence on eco-environment under climatic change and human activity in the south of Tarim Basin. *Arid Land Geography*, 25(1): 16–23. (in Chinese)
- Mao H R, Wang G C, Liao F. 2022. Geochemical evolution of groundwater under the influence of human activities: A case study in the southwest of Poyang Lake Basin. *Applied Geochemistry*, 140: 105299, doi: 10.1016/j.apgeochem.2022.105299.
- Mohallel S A, Gomaa M A. 2017. Studying the impacts of groundwater evolution on the environment, west Qena City, Egypt. *Arabian Journal of Geosciences*, 10(16): 372, doi: 10.1007/s12517-017-3151-5.
- Pradeep G, Krishan G. 2022. Groundwater and agriculture potential mapping of Mewat District, Haryana, India. *Discover Water*, 2: 11, doi: 10.1007/s43832-022-00019-5.
- Qin G Q, Ling J S, Chen M, et al. 2021. The Evolution of Underground Water Resources in the Plain Area of Tuha Basin in the Past 60 Years and Its Trend Analysis. Urumqi: Xinjiang Water Resources and Hydropower Survey Design and Research Institute Co., Ltd., 268–269. (in Chinese)
- Ren D Y, Xu X, Huang Q Z, et al. 2018. Analyzing the role of shallow groundwater systems in the water use of different land-use types in arid irrigated regions. *Water*, 10(5): 634, doi: 10.3390/w10050634.
- Ren Z X, Yang D Y. 2007. Impacts of climate change on agriculture in the arid region of northwest China in recent 50 years. *Journal of Arid Land Resources and Environment*, 21(8): 48–53. (in Chinese)
- Scanlon B R, Reedy R C, Gates J B. 2010. Impact of agroecosystems on groundwater resources in the Central High Plains, USA. *Agricultural, Ecosystem & Environment*, 139(4): 700–713.
- Secchi D, Tanda M G, D’Oria M D, et al. 2022. Impacts of climate change on groundwater droughts by means of standardized indices and regional climate models. *Journal of Hydrology*, 603: 127154, doi: 10.1016/j.jhydrol.2021.127154.

- Shang S S, Lian L S, Ma T, et al. 2018. Spatiotemporal variation of temperature and precipitation in northwest China in recent 54 years. *Arid Zone Research*, 35(1): 68–76. (in Chinese)
- Shang Z, Tang Y, Yang S S. 2020. Analysis of groundwater dynamic characteristics and influencing factors in Turpan basin in recent 30 years. *Journal of China Institute of Water Resources and Hydropower Research*, 18(3): 192–203. (in Chinese)
- Sheng Z P. 2013. Impacts of groundwater pumping and climate variability on groundwater availability in the Rio Grande Basin. *Ecosphere*, 4(1): 1–25.
- Shi J S, Li G M, Liang X. 2014. Mechanism and regulation of groundwater evolution in the North China Plain. *Acta Geoscientica Sinica*, 35(5): 527–534. (in Chinese)
- Su H C, Wei W S, Han P. 2003. Changes in air temperature and evaporation in Xinjiang during recent 50 years. *Journal of Glaciology and Geocryology*, 25(2): 174–178. (in Chinese)
- Sun Q Y, Guo H, Lu C Y. 2021. Current status and development trend of groundwater dynamic evolution research. *Journal of Irrigation and Drainage*, 40(S1): 58–64. (in Chinese)
- Trásy-Havril T, Szkolnikovics-Simon S, Mádl-Szőnyi J. 2022. How complex groundwater flow systems respond to climate change induced recharge reduction. *Water*, 14(19): 3026, doi: 10.3390/w14193026.
- Wang L S, Yue L L, Tang Z J, et al. 2014. Influence of climate change and agricultural development on groundwater level in Shiyang river basin. *Transactions of the Chinese Society for Agricultural Machinery*, 45(1): 121–128. (in Chinese)
- Wang S J, Zhang S M, Deng M J, et al. 2010. *Complete Book of Rivers and Lakes in Xinjiang, China*. Beijing: China Water Resources and Hydropower Press, 223–224. (in Chinese)
- Wang Y X, Li X. 1997. Studies on sustainable utilization of water resources in the Turpan basin. *Journal of Arid Land Resources and Environment*, 11(3): 9–14. (in Chinese)
- Warku F, Korme T, Wedajo G K. 2022. Impacts of land use/cover change and climate variability on groundwater recharge for upper Gibe watershed, Ethiopia. *Sustainable Water Resources Management*, 8(1): 19–34.
- Wei Y, Wang F, Hong B, et al. 2023. Revealing spatial variability of groundwater level in typical ecosystems of the Tarim Basin through ensemble algorithms and limited observations. *Journal of Hydrology*, 620: 129399, doi: 10.1016/j.jhydrol.2023.129399.
- Wu B, Du M L, Yang P N. 2016. Evolution of groundwater recharge and discharge in Shanshan County in the last 60 years in relation to the attenuation

of flow in the karez well. *Transactions of the Chinese Society of Agricultural Engineering*, 32(16): 102–108. (in Chinese)

Wu B, Du M L, Mu Z X, et al. 2021. Analysis on the variation of groundwater resources and influencing factors in Xinjiang plain area from 1956 to 2016. *Advances in Water Science*, 32(5): 659–669. (in Chinese)

Yang S M, Chu X Z, Zhang Y. 2018. Analysis on characteristics of temperature and precipitation change in Turpan city in recent 65 years. *Ecological Science*, 37(3): 44–50. (in Chinese)

Ye Y X, Du L J, Zhang B Z, et al. 2014. Analysis on feature of climate and runoff evolution in Turpan and its surrounding areas. *Journal of Water Resources & Water Engineering*, 25(6): 61–67. (in Chinese)

Yoshihisa U. 2004. Final Report of the Project on Sustainable Study of Groundwater Resources in the Turpan Basin, Xinjiang, People's Republic of China. Tokyo: Nippon Kokusai Kaisha Co., 352–367. (in Chinese)

Zhang J Y, Wang G Q, Jin J L, et al. 2020. Evolution and variation characteristics of the recorded runoff for the major rivers in China during 1956–2018. *Advances in Water Science*, 31(2): 153–161. (in Chinese)

Zhang M J, Liu J, Xie N. 2013. Report on Groundwater Exploration in the Turpan Basin, Xinjiang. Urumqi: The First Brigade of Hydrogeology, Xinjiang Bureau Geo-exploration & Mineral Development, 56–57. (in Chinese)

Zhou W B, Shi J L, Yang L H. 2007. *Groundwater Utilization*. Beijing: China Water Resources and Hydropower Press, 67–71. (in Chinese)

Note: Figure translations are in progress. See original paper for figures.

Source: ChinaXiv — Machine translation. Verify with original.