

Subsurface irrigation with ceramic emitters improves wolfberry yield and economic benefits on the Tibetan Plateau, China Postprint

Authors: HAN Mengxue, ZHANG Lin, LIU Xiaoqiang

Date: 2023-11-13T00:00:00+00:00

Abstract

Climate warming has led to the expansion of arable land at high altitudes, but it has also increased the demand for water use efficiency (WUE). To address this issue, the development of water-saving irrigation technology has become crucial in improving water productivity and economic returns. This study aimed to assess the impacts of three irrigation methods on water productivity and economic returns in wolfberry (*Lycium barbarum* L.) cultivation on the Tibetan Plateau, China during a two-year field trial. Results showed that subsurface irrigation with ceramic emitters (SICE) outperformed surface drip irrigation (DI) and subsurface drip irrigation (SDI) in terms of wolfberry yield. Over the two-year period, the average yield with SICE increased by 8.0% and 2.3% compared with DI and SDI, respectively. This improvement can be attributed to the stable soil moisture and higher temperature accumulation achieved with SICE. Furthermore, SICE exhibited higher WUE, with 14.6% and 4.5% increases compared with DI and SDI, respectively. In addition to the agronomic benefits, SICE also proved advantageous in terms of economic returns. Total average annual input costs of SICE were lower than the other two methods starting from the 8th year. Moreover, the benefit-cost ratio of SICE surpassed the other methods in the 4th year and continued to widen the gap with subsequent year. These findings highlight SICE as an economically viable water-saving irrigation strategy for wolfberry cultivation on the Tibetan Plateau. Thus, this research not only provides an effective water-saving irrigation strategy for wolfberry cultivation but also offers insights into addressing irrigation-related energy challenges in other crop production systems.

Full Text

Preamble

Journal of Arid Land (2023) 15(11): 1376-1390

<https://doi.org/10.1007/s40333-023-0034-3>

Subsurface irrigation with ceramic emitters improves wolfberry yield and economic benefits on the Tibetan Plateau, China

HAN Mengxue¹, ZHANG Lin^{2*}, LIU Xiaoqiang³

¹ College of Water Resources and Architectural Engineering, Northwest A&F University, Yangling 712100, China

² Department of Foreign Languages, Northwest A&F University, Yangling 712100, China

³ Department of Foreign Languages, Northwest A&F University, Yangling 712100, China

*Corresponding author: ZHANG Lin (E-mail: zlgc0201@163.com)

Received 2023-06-20; revised 2023-10-10; accepted 2023-10-27

© Xinjiang Institute of Ecology and Geography, Chinese Academy of Sciences, Science Press and Springer-Verlag GmbH Germany, part of Springer Nature 2023

Abstract

Climate warming has led to the expansion of arable land at high altitudes, but it has also increased the demand for water use efficiency (WUE). To address this issue, the development of water-saving irrigation technology has become crucial for improving water productivity and economic returns. This study aimed to assess the impacts of three irrigation methods on water productivity and economic returns in wolfberry (*Lycium barbarum* L.) cultivation on the Tibetan Plateau, China, during a two-year field trial. Results showed that subsurface irrigation with ceramic emitters (SICE) outperformed surface drip irrigation (DI) and subsurface drip irrigation (SDI) in terms of wolfberry yield. Over the two-year period, the average yield with SICE increased by 8.0% and 2.3% compared with DI and SDI, respectively. This improvement can be attributed to the stable soil moisture and higher temperature accumulation achieved with SICE. Furthermore, SICE exhibited higher WUE, with 14.6% and 4.5% increases compared with DI and SDI, respectively. In addition to the agronomic benefits, SICE also proved advantageous in terms of economic returns. Total average annual input costs of SICE were lower than the other two methods starting from the 8th year. Moreover, the benefit-cost ratio of SICE surpassed the other methods in the 4th year and continued to widen the gap in subsequent years. These findings highlight SICE as an economically viable water-saving irrigation strategy for

wolfberry cultivation on the Tibetan Plateau. Thus, this research not only provides an effective water-saving irrigation strategy for wolfberry cultivation but also offers insights into addressing irrigation-related energy challenges in other crop production systems.

Keywords: irrigation system; soil water content; soil temperature; water use efficiency; economic benefit

1 Introduction

In recent years, temperature increases associated with global warming in high-altitude areas have met the heat requirements of crops, leading to the reclamation of increasingly more land in these regions [?, ?]. The Tibetan Plateau, being the highest plateau in the world, has experienced an increase in arable land from 956 km² in 1990 to 2180 km² in 2020 [?, ?]. This expansion in agricultural land area means that more irrigation water is needed to meet the demands of agricultural production. However, due to the impacts of climate change, water resources on the Tibetan Plateau are decreasing annually [?]. The increasing demand for water resources coupled with decreasing water reserves not only limits local agricultural production but also threatens water security in downstream areas [?, ?]. Improving the efficiency of local agricultural water resource utilization represents an important measure to alleviate the imbalance between water supply and demand.

The application of water-saving irrigation techniques has contributed to enhanced WUE [?]. Two widely used irrigation techniques in China are deficit regulation irrigation and alternate root zone irrigation [?]. By regulating water allocation, these techniques reduce crop water consumption without causing noticeable declines in yield, increasing WUE by more than 25% and 41% for deficit regulation irrigation and alternate root zone irrigation, respectively, compared with adequate irrigation [?]. However, these techniques are frequently combined with drip irrigation and pump systems, which may limit their use in high-altitude areas due to high operational energy consumption and difficult energy supply [?, ?]. In addition, although water-saving irrigation has potential to generate significant ecological and social benefits [?, ?], farmers are usually more concerned about its impact on individual economic benefits [?]. Therefore, cost-effective and low-power approaches to increase water productivity should be considered.

A low-pressure subsurface irrigation with ceramic emitters (SICE) technique developed by [?] relies on soil water potential differences as irrigation drivers, reducing pressure in the irrigation system and contributing to lower energy consumption and operating costs. According to experiments and simulations, SICE would spontaneously and consistently irrigate with “just the right amount,” maintaining soil water content within a small range [?]. This stable and continuous water supply facilitates improved crop production and simplified field manage-

ment [?, ?]. In addition, SICE exhibited significant insulation properties during occasional temperature drops [?], which may assist in temperature accumulation for crops to obtain greater yields in high-altitude areas. Therefore, this study was conducted on wolfberry irrigated with SICE technique and aimed to determine: (1) the validity of SICE, and (2) an economic irrigation strategy for wolfberry cultivation on the Tibetan Plateau, China.

2.1 Study area

The experiment was performed in Hoit Taria Town, Qinghai Province, north-eastern Tibetan Plateau, China (37°21 N, 96°44 E; 2869 m a.s.l.). The region has an arid climate, with an annual precipitation of about 200 mm, more than 70% of which falls between June and September, and over 3000 h of sunshine per year with strong evaporation. The weather is very hot in summer and cold in winter, with a frost-free period of approximately 97 days. According to the International Soil Classification System, the soil type in this area is loamy sand. The physical properties are shown in Table 1. The reproductive period division of wolfberry and meteorological data in 2018 and 2019 are shown in Table 2.

Table 1 Soil particle composition of the study area

Soil depth	Bulk density (g/cm ³)	Porosity	Field capacity (cm ³ /cm ³)
0-20 cm	1.60±0.08	39.64±1.71	0.16±0.01
20-40cm	1.71±0.07	35.57±2.02	0.18±0.01
40-60cm	1.50±0.08	38.54±1.71	0.16±0.01

Note: Mean±SD; n=3.

Table 2 Growth period division of wolfberry in 2018 and 2019

Growth period	2018	2019
	Accumulated precipitation (mm)	Average daily temperature (°C)
Germination stage	6 May-10 Jun	11 Jun-14 Jul
Vegetative stage	11 Jun-14 Jul	15 Jul-4 Aug
Full-bloom stage	15 Jul-4 Aug	5 Aug-1 Sep
Summer harvest stage	5 Aug-1 Sep	2 Sep-22 Sep
Autumn harvest stage	2 Sep-22 Sep	Whole growth period
Whole growth period		

2.2 Experimental design

The experiment was conducted in a plantation from 2018 to 2019, with 3-4-year-old wolfberry trees planted at 0.8 m and 1.2 m spacing. Three types of irrigation were used: surface drip irrigation (DI), subsurface drip irrigation (SDI), and subsurface irrigation with ceramic emitters (SICE; Fig. 1a [Figure 1: see original paper]). DI was supplied by a traditional pump system, adopting the Netafim patch type with sprinkler flow and spacing of 1.10 L/h and 30 cm, respectively. Its irrigation schedule used the experience of local plantations over many years, which involved irrigating when soil moisture reached 60% of field capacity, with an irrigation amount of 182 mm throughout the entire growth period. The same schedule was implemented for SDI.

SICE used a special water supply system (Fig. 1b and c), which was divided into two parts: a storage tank (80 L) and a supply tank (30 L). The storage tank was used to meet water requirements for continuous irrigation, and the supply tank (equipped with a floating ball valve inside) was used to maintain constant pressure in the irrigation pipe. A scale was marked on the water storage tank to record water consumption. Meanwhile, to avoid blockages caused by long periods of continuous irrigation, we fitted SICE pipes with venting valves at the end, with manual flushing before and after irrigation. To ensure consistent irrigation volume under different irrigation methods, we set irrigation spacing and flow rate to be 20 cm and 0.30 L/h, respectively, for the SICE treatment. Moreover, depending on soil type and root system distribution of wolfberry [?], we installed the subsurface pipes of SDI and SICE at a depth of 30 cm (Fig. 1b). Each treatment used a pipeline to irrigate 50 trees and was replicated three times. All treatments were subjected to similar agronomic methods (such as mulching, trimming, and weeding).

Fig. 1 Subsurface irrigation with ceramic emitters (SICE) irrigation system (a), and layout of subsurface irrigation (b) with ceramic emitters (c).

2.3.1 Soil water content (SWC) and evapotranspiration (ET)

SWC and soil temperature at depths of 0-100 cm were measured every 15 days throughout the growth period, with an additional measurement when irrigation occurred. After evaluation of site-specific calibration equations by oven drying method, SWC and temperature of 0-20, 20-40, 40-60, 60-80, and 80-100 cm soil depths were measured using a time-domain reflectometry downhole sensor (TRIME-PICO-IPH, IMKO, Ellingen, Germany). Since more than 75% of wolfberry fine roots are distributed within 0-60 cm of soil [?], SWC was discussed for 0-60 and 60-100 cm soil depths.

The following formula was used to calculate soil water storage (SWS, mm):

$$SWS = SWC \times SD$$

where SWC is the soil water content (%); and SD is the thickness of soil depth (mm).

A soil water balance equation was used to calculate evapotranspiration (ET):

$$ET = I + P + U - D - \Delta SWS$$

where ET is the crop evapotranspiration during the wolfberry growth period (mm); I is the irrigation amount (mm); P is the effective rainfall (>5 mm) measured by an automatic weather station (mm) [?]; U is the water movement from deep soil into root zone, which was assumed to be zero in this study as the groundwater table was deeper than 50 m (mm); D is the deep percolation, which is calculated by subtracting soil water content above field capacity from total amount of soil water in root zone (mm); and ΔSWS is the change in soil water content from the beginning to the end of reproductive period in the 0-100 cm soil layer (%).

2.3.2 Growth parameters

Plant height, ground diameter, and leaf area index (LAI) were measured at 15-20 day intervals throughout the growth period of wolfberry. Plant height was measured from the highest point of the main stem to ground with a tapeline; ground diameter was measured with a vernier caliper at 10 cm of main stem from soil surface; and LAI was measured by the LAI-2200C plant canopy analyzer (LI-COR Inc., Lincoln, Nebraska, USA). Meanwhile, LAI and ET were used to estimate the inter-plant evapotranspiration [?]:

$$Es = ET \times e^{-1.21 \times LAI^{0.70}}$$

where Es is the inter-plant evaporation (mm); and LAI is the leaf area index.

2.3.3 Yield (Y) and water use efficiency (WUE)

At harvest stage, twelve plants were randomly selected in each treatment to determine dried fruit yield. WUE was calculated as:

$$WUE = \frac{Y}{ET}$$

where WUE is the water use efficiency ($\text{kg}/(\text{hm}^2 \cdot \text{mm})$); and Y is the dried fruit yield (kg/hm^2) [?].

2.4 Economic benefit

Economic benefit is a comprehensive indicator of economic activity, which can be expressed in terms of irrigation water productivity (IWP) and benefit cost ratio (BCR) [?]. In addition, we did not calculate all economic inputs (such as the cost of planting trees, pesticides, etc.) in this trial, and focused on the relationship between irrigation system inputs and benefits.

$$IWP = \frac{Cs \times Y}{I}$$

$$BCR = \frac{\sum_{t=1}^n \frac{Cs \times Y}{(1+r)^t}}{\sum_{t=1}^n \frac{Ct}{(1+r)^t}}$$

where IWP is the irrigation water productivity that indicated by gross return divided by irrigation water supplied to wolfberry (CNY/m^3); Cs is the selling price of wolfberry (CNY/kg); BCR is the benefit cost ratio, which attempts to determine the relationship between benefits and costs of growing wolfberries in irrigation systems (when $BCR > 1$, economic benefit reaches acceptable levels); Ct is the annual total cost (CNY); r is the social discount rate; t is the variable of year; and n is the total number of years to be included in the cumulation.

A costing method for micro-irrigation systems was devised by [?]. The total costs are calculated as sum of capital costs, operating costs, and water costs:

$$Ct = C_{\text{annual}} + C_{\text{operating}} + C_{\text{water}}$$

where C_{annual} is the annual capital cost (CNY); $C_{\text{operating}}$ is the operating cost (CNY); and C_{water} is the water cost (CNY).

Considering interest rate i, capital recovery factor (CRF), and irrigated area, total capital cost can be converted to annual capital cost [?]:

$$C_{\text{annual}} = Ci \times CRF = Ci \times \frac{i(1+i)^n}{(1+i)^n - 1}$$

where i is the interest rate; and Ci is the total capital cost (CNY).

Total capital cost is determined by costs of pipes (C_p), emitters (C_e), pump system (C_{pu}), and ditch (C_d).

Pipe cost is defined as:

$$C_p = V \times \rho_m \times C$$

$$V = \pi \times e \times (D + e) \times L$$

where V is the pipe material volume (m^3); m is the density of pipe material (kg/m^3); C is the cost per unit weight (CNY/kg); e is the pipe wall thickness (mm); D is the pipe internal diameter (mm); and L is the pipe length (m).

The required e is defined as:

$$e = \frac{r_w \times H_a \times D}{2\sigma}$$

where σ is the allowable pipe stress (kPa); r_w is the weight of water per unit volume (N/m^3); and H_a is the allowable pipe pressure (m).

Emitter cost is defined as:

$$C_e = \frac{A}{S_e \times S_r} \times C_{ei}$$

where A is the irrigated area (hm^2); S_e and S_r are the plant spacing and row spacing of wolfberry (m), respectively; and C_{ei} is the emitter unit price (CNY).

Drip irrigation costs from C_{pu} account for around 9% of total capital cost and this can be approximated as 10% of pipe cost [?, ?]. As the SICE pump system is simple, it is approximated at 1% of pipe cost. C_d can be considered as the ditching cost of subsurface irrigated farmland.

The annual Coperating was calculated as:

$$C_{operating} = P_m \times O_t \times C_{energy}$$

where P_m is the electric motor power required (kW); O_t is the irrigation system annual operating time (h); and C_{energy} is the energy unit price ($\text{CNY}/(\text{kW} \cdot \text{h})$).

Gross irrigation water per year was determined by actual water applied. It will be equal to I and the water cost (C_{water}) was calculated as:

$$C_{water} = I \times P_{water}$$

where P_{water} is the cost of obtaining water from the source (CNY/m^3), which depends on water availability and the initial water energy.

2.5 Statistical analysis

The effects of different irrigation methods on soil moisture, soil temperature, crop growth, and yield were assessed by one-way analysis of variance (ANOVA) followed by least significant difference (LSD) test, with $P < 0.05$ level considered statistically significant. All statistical analyses were performed using SPSS Statistics v.18.0 (IBM Corporation, Armonk, NY, USA). Figures were drawn using the Origin 2016 software (Origin Lab, Northampton, MA, USA).

3.1 Soil water content

Dynamics of mean SWC over time in different soil layers are shown in Figure 2 [Figure 2: see original paper]. In the 0–60 cm soil depth, SWC of DI and SDI showed alternating wet and dry status throughout the reproductive period, with SWC rising rapidly from 10.8% to 16.2% during irrigation, which equated to 60%–90% field capacity (FC), then gradually declining to the pre-irrigation state, repeating several times. The mean coefficient of variation (CV) in 2018 and 2019 for DI and SDI was 20.3% and 17.5%, respectively. In contrast, SWC for SICE remained at 10.4%–14.8% (57.9%–82.0% FC) due to differences in irrigation regimes, and CV was 8.9%, which remained stable compared with DI and SDI. In the 60–100 cm soil depth, SWC of DI and SDI fluctuated between 8.2%–12.6% and 8.9%–13.1%, with mean values greater than 10.0%. Meanwhile, SICE remained at 8.8%–10.7% and stayed close to the initial state. In addition, because there was very little rainfall in the area and minor variations in climate between the two test periods, the alterations in SWC were similar for the same treatment in both test periods.

Fig. 2 Variations of soil water content in depths of 0–60 (a) and 60–100 cm (b) over different growth stages. DI, surface drip irrigation; SDI, subsurface drip irrigation; SICE, subsurface irrigation with ceramic emitters. Bars are standard errors.

3.2 Soil temperature

Average soil temperature variations in 0–60 cm soil depth at different stages in 2018 are shown in Figure 3 [Figure 3: see original paper]. There was a lag between soil and atmospheric temperatures at daily scales, with soil temperatures starting to rise after 12:00 (LST) and atmospheric temperatures often before 10:00. Meanwhile, soil temperature variation range (R) was obviously smaller than air temperature because the specific heat capacity of soil was greater than that of air, and DI (R=3.8) was significantly higher than SDI (R=2.0) and SICE (R=0.8) as influenced by soil moisture. Additionally, the difference in daily cumulative temperature among the three treatments decreased as temperature rose. At the full-bloom stage, temperature of DI was only about 0.2°C

and 0.8°C less than those of SDI and SICE. From the whole growth period perspective, average daily temperature of SICE increased by 1.3°C and 0.9°C compared with DI and SDI, with growth rates of 7.1% and 5.2%, respectively.

Fig. 3 Soil temperature variations in 0–60 cm soil depth at different growth stages in 2018. (a) germination stage; (b) vegetative stage; (c) full-bloom stage; (d) summer harvest stage; (e) autumn harvest stage; (f) whole growth period. DI, surface drip irrigation; SDI, subsurface drip irrigation; SICE, subsurface irrigation with ceramic emitters; LST, local standard time. Bars are standard errors.

3.3 ET and soil evaporation

Average daily ET and soil evaporation for each treatment at different stages in 2018 and 2019 are shown in Figure 4 [Figure 4: see original paper]. DI and SDI had the same ET variation pattern at different stages, decreasing from germination stage to full-bloom stage (from 2.1 to 1.2 mm), with a large increase at summer harvest stage and then continuing to decrease (from 2.6 to 1.3 mm). In contrast, ET of SICE increased continuously from germination stage to summer harvest stage (approximately from 1.4 to 2.7 mm), and then began to decline. Notably, ET of SICE was significantly lower than those of DI and SDI at germination stage due to irrigation regime, with decreases of 32.8% and 29.7% in 2018 and 2019, respectively. However, due to differences in crop growth, SICE increased by 44.6% and 53.0% compared with DI and SDI at full-bloom stage. Meanwhile, the highest ET values of DI, SDI, and SICE all occurred at summer harvest stage, accounting for 28.3%, 28.2%, and 30.8% of the total ET, respectively. Moreover, soil evaporation changes among the three treatments were generally consistent, showing a decreasing trend at summer harvest stage. Soil evaporation values of DI and SDI were larger at germination stage and summer harvest stage, accounting for 12.8% and 12.2% of the total ET for DI, and 12.4% and 11.3% for SDI, respectively. SICE only had large soil evaporation at summer harvest stage, accounting for 11.7% of the total ET.

Fig. 4 Average daily evapotranspiration (ET, a and b) and soil evaporation (c and d) for each treatment at different stages in 2018 and 2019. Different lowercase letters within the same stage indicate significant differences among different treatments at $P < 0.05$ level. Harvest (s), summer harvest stage; Harvest (a), autumn harvest stage; DI, surface drip irrigation; SDI, subsurface drip irrigation; SICE, subsurface irrigation with ceramic emitters. Bars are standard errors.

3.4 Growth parameters, yield, and WUE

Variations of plant height, ground diameter, and LAI for wolfberry in 2018 and 2019 are shown in Figure 5 [Figure 5: see original paper]. Plant height and ground diameter increased as wolfberry grew, while LAI peaked at the summer harvest stage and then gradually decreased. Among the treatments of DI, SDI, and SICE, plant height was affected by pruning, and there were only significant differences at the end of reproduction. However, the differences in ground diameter and LAI were obvious, with a slight decrease in growth parameters at full-bloom stage found for DI and SDI. During the two-year experiment, the highest plant growth was found for SICE. Average ground diameter of DI increased by 2.84 mm, and they were 3.01 and 3.24 mm for SDI and SICE, respectively. Average LAI peaked at 1.37 for DI, and they were 1.46 and 1.52 for SDI and SICE, respectively.

Yield and WUE followed a similar pattern to wolfberry growth between treatments (Table 3). Average yield and WUE of DI were 2788.1 kg/hm² and 10.6 kg/(hm² · mm), 2944.0 kg/hm² and 11.7 kg/(hm² · mm) for SDI, and 3012.5 kg/hm² and 12.2 kg/(hm² · mm) for SICE, respectively. Yield of SICE increased by 8.0% and 2.3%, and WUE increased by 14.6% and 4.5% compared with those of DI and SDI.

Fig. 5 Growth parameters of wolfberry at different stages in 2018 (a-c) and 2019 (d-f). LAI, leaf area index. DI, surface drip irrigation; SDI, subsurface drip irrigation; SICE, subsurface irrigation with ceramic emitters. Bars are standard errors.

Table 3 Yield and WUE of wolfberry for each treatment in 2018 and 2019

Treatment	ET (mm)	Yield (kg/hm ²)	WUE (kg/(hm ² · mm))
2018			
DI	256.4a	2931.5c	11.4c
SDI	246.2b	3126.4b	12.7b
SICE	242.6b	3199.6a	13.2a
2019			
DI	269.4a	2644.8c	10.6b
SDI	259.9b	2761.5b	11.3a
SICE	252.7b	2844.4a	11.3a

Note: WUE, water use efficiency; ET, evapotranspiration; DI, surface drip irrigation; SDI, subsurface drip irrigation; SICE, subsurface irrigation with ceramic emitters. Different lowercase letters within the same year indicate significant differences at $P < 0.05$ level.

3.5 Economic benefit

Tables 4 and 5 show the input data and pipeline characteristics required to calculate local capital costs. Economic revenues and expenditures for DI, SDI, and SICE were calculated from the above data as shown in Table 6. The costs and economic benefits over 10 years were estimated in Figure 6 [Figure 6: see original paper].

Among input costs, SICE emitters cost approximately 2.8 times more than DI and SDI, increasing by 3819.6 CNY/hm², but construction costs for the pump system reduced by 1262.8 CNY. Meanwhile, taking into account the depreciation and operation of the irrigation system, total annual cost of SICE was less than SDI from the 3rd year onwards and less than DI from the 8th year onwards. In addition, all three irrigation methods recovered the irrigation investment in the first year when planted with wolfberries. SICE offered considerable economic benefits due to increased yield, which increased IWP by 8.0% and 2.5% compared with DI and SDI. BCR of SICE exceeded that of SDI in the 2nd year and DI in the 4th year. Compared with DI and SDI, BCR of SICE increased to 4.7% and 6.9% in the 5th year, and in the 10th year, it reached 13.5% and 14.9% (Fig. 6).

Table 4 Input data for economic calculation

Parameter	Value
Se-DI,SDI (m)	0.3
Se-SICE (m)	0.2
Sr (m)	1.2
Pw (CNY/m ³)	0.5
Pm (kW)	2.2
Ot (h)	120
I (m ³ /hm ²)	1820
Cei-DI,SDI (CNY/unit)	0.3
Cei-SICE (CNY/unit)	0.85
Cs (CNY/kg)	40
Cenergy (CNY/(kW · h))	0.6
Cd (CNY/hm ²)	1500
r	0.08
i	0.05

Note: Se-DI,SDI and Se-SICE are the emitter spacing of DI, SDI, and SICE, respectively; Sr, row spacing of wolfberry; Pw, cost of obtaining water from source; Pm, electric motor power required; Ot, irrigation system annual operating time; I, irrigation amount; Cei-DI,SDI and Cei-SICE are the emitter unit price of DI, SDI and SICE, respectively; Cs, selling price of wolfberries; Cenergy, energy unit price; Cd, cost of ditch; r and i are the social discount rate and interest rate, respectively.

Table 5 Pipeline characteristics for determining capital cost

Parameter	Lateral	Manifold
m (kg/m ³)	950	950
C (CNY/kg)	12	12
H_a (m)	10	10
σ (kPa)	2500	2500

Note: m , density of pipe material; C , cost per unit weight; H_a , allowable pipe pressure; σ , allowable pipe stress.

Table 6 Cost, income, and economic efficiency

Parameter	DI	SDI	SICE
C_p (CNY)	12,928.6	12,928.6	11,682.5
C_e (CNY)	15,749.3	17,249.3	18,559.9
C_{pu} (CNY)	83,643.8	88,318.5	90,375.0
C_d (CNY)	1,500	1,500	1,500
C_i (CNY)	113,821.7	119,996.4	122,117.4
Annual (CNY)	14,734.9	15,533.5	15,808.0
Operating (CNY)	158.4	158.4	7.9
C_{water} (CNY)	910.0	910.0	910.0
$C_s \times Y$ (CNY)	111,524.0	117,760.0	120,500.0
Irrigation water productivity (CNY/m ³)	61.3	64.7	66.2

Note: DI , surface drip irrigation; SDI , subsurface drip irrigation; $SICE$, subsurface irrigation with ceramic emitters; C_p , cost of pipes; C_e , cost of emitters; C_{pu} , cost of pump system; C_d , cost of ditch; C_i , total capital cost; $C_{operating}$, operating cost of irrigation system. Considering $SICE$ irrigation pressure is 5% of DI and SDI , the operating cost is also estimated at 5% of DI and SDI ; C_{water} , cost of water; C_s , selling price of wolfberry; Y , dried fruit yield of wolfberry, and estimated as the average yield of a two-year experiment.

Fig. 6 Estimated cost (C_t) and economic efficiency over 10 years. DI , surface drip irrigation; SDI , subsurface drip irrigation; $SICE$, subsurface irrigation with ceramic emitters.

4.1 Soil hydrothermal environment

Soil hydrothermal conditions are important factors affecting crop growth in arid areas [?], which are further enhanced at high altitudes due to heavy evaporation and temperature differences [?, ?]. Influenced by irrigation schedule, SWC

showed a clear alternation between wet and dry in DI and SDI, and small fluctuations in SICE. These trends are generally consistent with other studies [?, ?]. DI and SDI had larger CV values in this study, about twice as high as SICE. At the end of irrigation, DI had the maximum horizontal wetting distance and SWC at soil surface, but due to water evaporation and redistribution, soil moisture significantly reduced until the next irrigation to refill [?, ?]. SDI had a saturated area in the soil when irrigation finished, which increased SWC in deeper soil although it reduced evaporation loss [?]. Meanwhile, soil water saturation would reduce the oxygen content, which had adverse effects on plant root growth and nutrient uptake [?]. These reasons decreased WUE of DI and SDI. In contrast, stable soil moisture conditions at SICE contributed to crop production [?], but the stable level of SWC also had to be considered. Adverse effects might also be caused when SWC was stable below or above specific thresholds that triggered severe drought stress or internal flooding [?]. In this trial, by designing multiple SICE treatments and selecting irrigation amounts consistent with DI and SDI, SWC was stable in the range of 10.4%-14.8% (57.9%-82.0% FC) and increased wolfberry yield.

Meanwhile, as an important medium for soil energy exchange, soil water influences the variation and accumulation of soil temperature [?]. Given that factors such as soil texture, topography, and temperature that influence soil temperature are consistent under the same experimental conditions, the variation in soil temperature was primarily caused by soil moisture level. During all stages, air temperature exerted a dominant influence on changes in soil temperature. Numerous studies have also corroborated that both water recharge and air temperature constitute pivotal factors affecting soil temperature [?, ?]. Moreover, SICE provided a greater specific heat capacity by keeping soil moisture for longer time; when soil temperature increased following air temperature, cumulative temperature differences between SICE and other treatments decreased. Previous studies showed that SICE provides better insulation during sudden changes in temperature [?]. However, since low temperatures are frequently observed at high altitudes [?], the lower soil temperature at high altitudes led to a reduction in water uptake by crop roots [?]. This study evaluated the influence of various irrigation methods on soil temperature over the complete growth period and determined that SICE was capable of sustaining soil temperature, mitigating cold stress, and fostering crop growth [?, ?].

4.2 Plant growth and evapotranspiration

Rapid and stable plant growth are important for yield [?]. In the two-year trial, three treatments had similar growth rates, but growth parameters of DI and SDI showed a sudden drop at full-bloom stage. We speculated that this was caused by imposed dormancy of wolfberry. Imposed dormancy means that growth is forced to be extremely slow or briefly quiescent when plants encounter adverse conditions such as low temperature and drought during reproductive stage [?].

This phenomenon was mainly manifested by branches withering, leaves falling, or main stem shrinking [?]. Because soil evaporation and plant transpiration rapidly depleted soil water after drip irrigation [?], temporary drought conditions occurred between wet and dry periods when employing drip irrigation. At the same time, full-bloom stage was characterized by low rainfall and high temperatures (Table 2), and water requirements were even more intense. Moreover, research indicated that vegetation ecosystem resistance at high altitudes is lower under extreme drought conditions [?]. These three reasons might have collectively contributed to the unstable growth of wolfberry under DI and SDI. On the contrary, due to continuous water supply and stable soil moisture environment, SICE improved soil drought conditions and inhibited imposed dormancy in wolfberry, resulting in higher growth parameters.

ET is an important basis for determining water management practices and designing irrigation systems and regimes [?, ?]. Understanding ET patterns during crop growth plays a crucial role in assessing irrigation practices. The most striking feature of this trial was that DI and SDI showed a decreasing trend in ET from germination stage to full-bloom stage, which appeared opposite to crop growth, while SICE showed a consistent trend in ET and crop growth. In general, crop ET should be rising in the early stages of growth [?]. This may be explained by the following two reasons. Firstly, irrigation strategies of DI and SDI were influenced by the combination of soil moisture condition and irrigation cycle, with plants being fully irrigated only when soil became fairly dry, which is common in commercial plant production [?]. DI and SDI were irrigated twice at the beginning of reproductive stage (germination stage) and only once at other growth stages (Fig. 2). Secondly, precipitation had little effect on the irrigation regime of DI and SDI due to poor soil texture and sparse rainfall. Therefore, as irrigation and rainfall decreased, ET of DI and SDI continued to decrease with wolfberry growth. As SICE adjusted outflow according to soil moisture conditions [?], we used reduced emitter output during rainfall in water shortage periods, which was equivalent to extended use of rainfall and increased availability of rainwater. Meanwhile, small and continuous water supply from SICE also contributed to limiting water evaporation and discharge, further improving WUE [?].

4.3 WUE and economic benefit

Increased WUE and economic benefit are important for improving the ecological environment, developing agricultural production, and raising incomes of farmers at high altitudes [?, ?]. In this experiment, SICE treatment had the highest WUE, perhaps due to several combined factors. Firstly, low temperatures tended to constrain crop yields at high altitudes [?], while the stable soil moisture maintained by SICE promoted more suitable soil temperatures for the growth of high-altitude crops. Secondly, water stress generated between alternate wet and dry cycles at the same irrigation amount resulted in reduced

growth and yield of wolfberry [?], while continuous water supply avoided imposed dormancy and enhanced wolfberry growth and accumulation. Thirdly and most importantly, SICE could autonomously adjust the emitter flow rate based on soil moisture conditions to increase WUE. Variable rate irrigation (VRI) technology also demonstrated that adapting water supply rates to soil and crop characteristics helped conserve water and improved WUE [?, ?, ?]. Depending on the combination of crops and weather conditions, VRI could lead to water savings of 10%-15% [?]. Although the SICE irrigation system does not use sophisticated monitoring equipment such as VRI [?], micro-regulation was achieved by reduced emitter outflow rate and continuous irrigation, and its feasibility has been verified in this experiment and other simulations [?]. However, this trial only considered the same irrigation amount for SDI and SICE as DI, while SDI and SICE still had the potential to improve water productivity by adjusting irrigation amount. Meanwhile, SICE requires more systematic simulation methods to determine the relationship between irrigation amount and SWC level.

Trying new water-saving irrigation methods requires an assessment of production costs and economic benefits, which will help farmers choose appropriate management practices [?]. In this trial, SICE required higher inputs in the initial construction, but due to low operating costs, the average annual input costs of SICE started to be lower than the other treatments from the 8th year onwards. Meanwhile, BCR of SICE treatment exceeded that of the other treatments from the 4th year onwards due to its relatively high yield. In addition, in sparsely populated high-altitude areas, labor is an important potential factor in agricultural production. In Ecuador, farmers have opted to use water-saving irrigation techniques in order to reduce the need for labor [?]. SICE only needs to design the parameters before irrigation, and operation management under continuous irrigation is simple. Reduced labor costs may further enhance the economic benefits of SICE. However, the cost of ceramic emitters is still much higher than plastic pipes due to preparation process and material formulation [?]. In this trial, the cost of SICE emitters increased by 3819.6 CNY/hm² compared with DI and SDI, representing 20.6% of its total capital cost. Thus, cheaper ceramic emitters should be considered in future designs.

5 Conclusions

A two-year field experiment was conducted to assess the performance of DI, SDI, and SICE in wolfberry cultivation on the Tibetan Plateau, China. The results indicated that SICE could provide a relatively stable soil moisture environment and increase the cumulative soil temperature under similar water consumption compared with DI and SDI. On this basis, SICE treatment enhanced the growth and yield of wolfberry by improving the hydrothermal environment. Moreover, SICE contributed to higher productivity and WUE in wolfberry cultivation on the Tibetan Plateau. Although SICE treatment required higher

initial investment, its lower operational costs caused it to gradually surpass DI and SDI treatments in terms of BCR over time. Therefore, SICE not only maintained economic return but also reduced the energy consumption for the irrigation system. In summary, this study verified the technical advantages of SICE, which included low pressure, low flow, and continuous irrigation features. Unfortunately, the study did not consider the integrated water-fertilizer effects under SICE treatment; hence, future research should pay more attention to the movement, absorption, and transformation of water and fertilizer under SICE treatment.

Conflict of interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Acknowledgements

This research was funded by the National Natural Science Foundation of China (52079131, 51779246). We would like to thank the editors and reviewers for their constructive feedback.

Author contributions

Conceptualization: HAN Mengxue, ZHANG Lin

Data curation: HAN Mengxue

Formal analysis: HAN Mengxue, ZHANG Lin

Funding acquisition: ZHANG Lin

Investigation: HAN Mengxue

Methodology: ZHANG Lin

Project administration: HAN Mengxue

Resources: ZHANG Lin

Supervision: ZHANG Lin, LIU Xiaoqiang

Validation: ZHANG Lin, LIU Xiaoqiang

Visualization: HAN Mengxue, LIU Xiaoqiang

Writing - original draft: HAN Mengxue

Writing - review & editing: HAN Mengxue, ZHANG Lin, LIU Xiaoqiang

References

- Abu-Hamdeh N H, Khdair A I, Reeder R C. 2001. A comparison of two methods used to evaluate thermal conductivity for some soils. *International Journal of Heat and Mass Transfer*, 44(5): 1073-1078.
- Allen R G, Pereira L S, Raes D, et al. 1998. Crop evapotranspiration-guidelines for computing crop water requirements-FAO Irrigation and drainage paper 56. Food and Agriculture Organization, Rome.
- Barnett T P, Adam J C, Lettenmaier D P. 2005. Potential impacts of a warming climate on water availability in snow-dominated regions. *Nature*, 438(7066): 303-309.
- Blaikie P M, Muldavin J S S. 2004. Upstream, downstream, China, India: The politics of environment in the Himalayan region. *Annals of the Association of American Geographers*, 94(3): 520-548.
- Cai Y, Wu P, Zhu D, et al. 2021. Subsurface irrigation with ceramic emitters: An effective method to improve apple yield and irrigation water use efficiency in the semi-arid Loess Plateau. *Agriculture Ecosystems & Environment*, 313: 107404, doi: 10.1016/j.agee.2021.107404.
- Cai Y, Wu P, Gao X, et al. 2022. Subsurface irrigation with ceramic emitters: Evaluating soil water effects under multiple precipitation scenarios. *Agricultural Water Management*, 272: 107851, doi: 10.1016/j.agwat.2022.107851.
- Cao Y, Zhang W, Ren J. 2020. Efficiency analysis of the input for water-saving agriculture in China. *Water*, 12(1): 207, doi: 10.3390/w12010207.
- Chen N, Zhang Y, Zu J, et al. 2020. The compensation effects of post-drought regrowth on earlier drought loss across the Tibetan Plateau grasslands. *Agricultural and Forest Meteorology*, 281: 107822, doi: 10.1016/j.agrformet.2019.107822.
- Colak Y B, Yazar A, Sesveren S, et al. 2017. Evaluation of yield and leaf water potential (LWP) for eggplant under varying irrigation regimes using surface and subsurface drip systems. *Scientia Horticulturae*, 219: 10-21.
- Dandy G C, Hassanli A M. 1996. Optimum design and operation of multiple subunit drip irrigation systems. *Journal of Irrigation and Drainage Engineering*, 122(5): 265-275.
- Darouich H M, Pedras C M G, Goncalves J M, et al. 2014. Drip vs. surface irrigation: A comparison focussing on water saving and economic returns using multicriteria analysis applied to cotton. *Biosystems Engineering*, 122: 74-90.
- Diamantopoulos E, Elmaloglou S. 2012. The effect of drip line placement on soil water dynamics in the case of surface and subsurface drip irrigation. *Irrigation and Drainage*, 61(5): 622-630.

- Ghorbanpour A, Salimi A, Ghanbary M A T, et al. 2018. The effect of *Trichoderma harzianum* in mitigating low temperature stress in tomato (*Solanum lycopersicum* L.) plants. *Scientia Horticulturae*, 230: 134-141.
- Grimalt J O, Borghini F, Sanchez-Hernandez J C, et al. 2004. Temperature dependence of the distribution of organochlorine compounds in the mosses of the Andean Mountains. *Environmental Science & Technology*, 38(20): 5386-5392.
- Guo L, Liu M, Zhang Y, et al. 2018. Yield differences get large with ascendant altitude between traditional paddy and water-saving ground cover rice production system. *European Journal of Agronomy*, 92: 9-16.
- Hafeez M, Bundschuh J, Mushtaq S. 2014. Exploring synergies and tradeoffs: Energy, water, and economic implications of water reuse in rice-based irrigation systems. *Applied Energy*, 114: 889-900.
- Jungqvist G, Oni S K, Teutschbein C, et al. 2014. Effect of climate change on soil temperature in Swedish Boreal Forests. *PLoS ONE*, 9(4): 93957, doi: 10.1371/journal.pone.0093957.
- Kang S, Cai H. 2002. *Theory and Practice of the Controlled Alternate Partial Root-zone Irrigation and Regulated Deficit Irrigation*. Beijing: China Agricultural Press. (in Chinese)
- Kang S, Hao X, Du T, et al. 2017. Improving agricultural water productivity to ensure food security in China under changing environment: From research to practice. *Agricultural Water Management*, 179: 5-17.
- Keller J, Bliesner R D. 1990. *Sprinkle and Trickle Irrigation*. New York: Van Nostrand Reinhold.
- Khorsand A, Rezaverdinejad V, Asgarzadeh H, et al. 2019. Irrigation scheduling of maize based on plant and soil indices with surface drip irrigation subjected to different irrigation regimes. *Agricultural Water Management*, 224(4): 105740, doi: 10.1016/j.agwat.2019.105740.
- Kool D, Agam N, Lazarovitch N, et al. 2014. A review of approaches for evapotranspiration partitioning. *Agricultural and Forest Meteorology*, 184: 56-70.
- Li C, Wen X, Wan X, et al. 2016. Towards the highly effective use of precipitation by ridge-furrow with plastic film mulching instead of relying on irrigation resources in a dry semi-humid area. *Field Crops Research*, 188: 62-73.
- Li M, Guo P. 2014. A multi-objective optimal allocation model for irrigation water resources under multiple uncertainties. *Applied Mathematical Modelling*, 38(19-20): 4897-4911.
- Li X, Long D, Scanlon B R, et al. 2022. Climate change threatens terrestrial water storage over the Tibetan Plateau. *Nature Climate Change*, 12(9): 801-807.

- Li Y, Wang L, Xue X, et al. 2017. Comparison of drip fertigation and negative pressure fertigation on soil water dynamics and water use efficiency of greenhouse tomato grown in the North China Plain. *Agricultural Water Management*, 184: 1-8.
- Liu H, Bi R, Guo Y, et al. 2021a. Protection zoning of cultivated land based on form-structure-function multidimensional evaluation system. *Transactions of the Chinese Society of Agricultural Machinery*, 52(2): 168-177. (in Chinese)
- Liu S, Wu F, Zai S, et al. 2021b. An optimized cloud model algorithm adapted to comprehensive benefit evaluation of water-saving irrigation. *Polish Journal of Environmental Studies*, 30(4): 3713-3726.
- Liu Z, Yao Z, Yu C, et al. 2013. Assessing crop water demand and deficit for the growth of spring highland barley in Tibet, China. *Journal of Integrative Agriculture*, 12(3): 541-551.
- Martinez J, Reza J. 2014. Water use efficiency of surface drip irrigation versus an alternative subsurface drip irrigation method. *Journal of Irrigation and Drainage Engineering*, 140(10): 04014030, doi: 10.1061/(ASCE)IR.1943-4774.000074.
- Mo F, Wang J, Xiong Y, et al. 2016. Ridge-furrow mulching system in semi-arid Kenya: A promising solution to improve soil water availability and maize productivity. *European Journal of Agronomy*, 80: 124-136.
- Mo F, Wang J, Zhou H, et al. 2017. Ridge-furrow plastic-mulching with balanced fertilization in rainfed maize (*Zea mays* L.): An adaptive management in east African Plateau. *Agricultural and Forest Meteorology*, 236: 100-112.
- Monjezi M S, Ebrahimian H, Liaghat A, et al. 2013. Soil-wetting front in surface and subsurface drip irrigation. *Proceedings of the Institution of Civil Engineers-Water Management*, 166(5): 272-284.
- Nam S, Kang S, Kim J. 2020. Maintaining a constant soil moisture level can enhance the growth and phenolic content of sweet basil better than fluctuating irrigation. *Agricultural Water Management*, 238: 106203, doi: 10.1016/j.agwat.2020.106203.
- Neupane J, Guo W, West C P, et al. 2021. Effects of irrigation rates on cotton yield as affected by soil physical properties and topography in the southern high plains. *PLoS ONE*, 16(10): 0258496, doi: 10.1371/journal.pone.0258496.
- Omary M, Camp C R, Sadler E J. 1997. Center pivot irrigation system modification to provide variable water application depths. *Applied Engineering in Agriculture*, 13(2): 235-239.
- Ozer H, Coban F, Sahin U, et al. 2020. Response of black cumin (*Nigella sativa* L.) to deficit irrigation in a semi-arid region: Growth, yield, quality, and water productivity. *Industrial Crops and Products*, 144: 112048, doi: 10.1016/j.indcrop.2019.112048.

- Pendergast L, Bhattarai S P, Midmore D J. 2019. Evaluation of aerated sub-surface drip irrigation on yield, dry weight partitioning and water use efficiency of a broad-acre chickpea (*Cicer arietinum* L.) in a vertosol. *Agricultural Water Management*, 217: 38–46.
- Powell J W, Welsh J M, Pannell D, et al. 2019. Can applying renewable energy for Australian sugarcane irrigation reduce energy cost and environmental impacts? A case study approach. *Journal of Cleaner Production*, 240(10): 118177, doi: 10.1016/j.jclepro.2019.118177.
- Provenzano G, Rodriguez-Sinobas L, Roldan-Canas J. 2014. Irrigated agriculture: Water resources management for a sustainable environment. *Biosystems Engineering*, 128: 1–3.
- Qi Z, Zhang T, Zhou L, et al. 2016. Combined effects of mulch and tillage on soil hydrothermal conditions under drip irrigation in Hetao Irrigation District, China. *Water*, 8(11): 504, doi: 10.3390/w8110504.
- Sadler E J, Evans R G, Stone K C, et al. 2005. Opportunities for conservation with precision irrigation. *Journal of Soil and Water Conservation*, 60(6): 371–379.
- Sui R, Yan H. 2017. Field study of variable rate irrigation management in humid climates. *Irrigation and Drainage*, 66(3): 421–428.
- Sui R, O' Shaughnessy S, Evett S R, et al. 2020. Evaluation of a decision support system for variable-rate irrigation in humid regions. *Transactions of the ASABE*, 63(5): 1207–1215.
- Tesfahunegn G B, Wortmann C S. 2008. Tie-ridge tillage for high altitude pulse production in northern Ethiopia. *Agronomy Journal*, 100(2): 447–453.
- Tharani K L, Dahiya R. 2018. Choice of battery energy storage for a hybrid renewable energy system. *Turkish Journal of Electrical Engineering and Computer Sciences*, 26(2): 666–676.
- Thomashow M F. 1999. Plant cold acclimation: Freezing tolerance genes and regulatory mechanisms. *Annual Review of Plant Physiology and Plant Molecular Biology*, 50: 571–599.
- Tuo Y, Wang Q, Zhang L, et al. 2022. Establishment of a crop evapotranspiration calculation model and its validation. *Journal of Agronomy and Crop Science*, 209(2): 251–260.
- Voltaire F, Norton M. 2006. Summer dormancy in perennial temperate grasses. *Annals of Botany*, 98(5): 927–933.
- Wang J, Gao X, Zhou Y, et al. 2020. Impact of conservation practices on soil hydrothermal properties and crop water use efficiency in a dry agricultural region of the Tibetan Plateau. *Soil & Tillage Research*, 200: 104619, doi: 10.1016/j.still.2020.104619.

Wang J, Zhu D, Zhang L, et al. 2015. Economic analysis approach for identifying optimal microirrigation uniformity. *Journal of Irrigation and Drainage Engineering*, 141(8): 04015002, doi: 10.1061/(ASCE)IR.1943-4774.000086.

Wu P, Cai Y, Zhang L, et al. 2021. *Research and Application of Subsurface Irrigation with Ceramic Emitters Technology*. Beijing: Science Publishing. (in Chinese)

Xie Y L, Xia D X, Ji L, et al. 2018. An inexact stochastic-fuzzy optimization model for agricultural water allocation and land resources utilization management under considering effective rainfall. *Ecological Indicators*, 92: 301–311.

Xu J, Grumbine R E, Shrestha A, et al. 2009. The melting Himalayas: Cascading effects of climate change on water, biodiversity, and livelihoods. *Conservation Biology*, 23(3): 520–530.

Yang L, Yan J, Wang P, et al. 2019. Impacts of climate change on the reclamation of farmers and herdsman in the Tibetan Plateau. *Journal of Ecology*, 39(10): 3655–3669.

Yang Y, Wu Z, He H, et al. 2018. Differences of the changes in soil temperature of cold and mid-temperate zones, Northeast China. *Theoretical and Applied Climatology*, 134(1-2): 633–643.

Zhang G, Dong J, Zhou C, et al. 2013. Increasing cropping intensity in response to climate warming in Tibetan Plateau, China. *Field Crops Research*, 142: 36–46.

Zhao J, Li H, Zhang C, et al. 2018. Physiological response of four wolfberry (*Lycium* Linn.) species under drought stress. *Journal of Integrative Agriculture*, 17(3): 603–612.

Zhou W, Zhang L, Wu P, et al. 2020. Preparation of SiO₂/Si₃N₄ ceramics with step gradient porosity and heavy metal ion adsorption. *Ceramics International*, 46(9): 13263–13271.

Note: Figure translations are in progress. See original paper for figures.

Source: ChinaXiv – Machine translation. Verify with original.