

Estimation and inter-comparison of infiltration models in the agricultural area of the Mitidja Plain, Algeria (Postprint)

Authors: Amina MAZIGHI

Date: 2023-12-20T00:00:00+00:00

Abstract

Infiltration is an important part of the hydrological cycle, and it is one of the main abstractions accounted for in the rainfall-runoff modeling. The main purpose of this study is to compare the infiltration models that were used to assess the infiltration rate of the Mitidja Plain in Algeria. Field infiltration tests were conducted at 40 different sites using a double ring infiltrometer. Five statistical comparison criteria including root mean squared error (RMSE), normalized root mean squared error (NRMSE), coefficient of correlation (CC), Nash-Sutcliffe efficiency (NSE), and Kling-Gupta efficiency (KGE) were used to determine the best performing infiltration model and to confirm anomalies between predicted and observed values. Then we evaluated performance of five models (i.e., the Philip model, Kostiaikov model, Modified Kostiaikov model, Novel model, and Horton model) in simulating the infiltration process based on the adjusted performance parameters cited above. Results indicated that the Novel model had the best simulated water infiltration process in the Mitidja Plain in Algeria. However, the Philip model was the weakest to simulate the infiltration process. The conclusion of this study can be useful for estimating infiltration rate at various sites using a Novel model when measured infiltration data are not available and are useful for planning and managing water resources in the study area.

Full Text

Preamble

Estimation and Inter-comparison of Infiltration Models in the Agricultural Area of the Mitidja Plain, Algeria

Amina MAZIGHI¹, Hind MEDDI¹, Mohamed MEDDI^{1*}, Ishak ABDI^{1,2}, Giovanni RAVAZZANI³, Mouna FEKI³

¹Department of Civil Engineering and Hydraulics, University of Jijel, Jijel 18000, Algeria

²Department of Civil Engineering and Hydraulics, University of Jijel, Jijel 18000, Algeria

³Department of Civil and Environmental Engineering, Polytechnic University of Milan, Milan 20133, Italy

Abstract: Infiltration is an important part of the hydrological cycle and one of the main abstractions accounted for in rainfall-runoff modeling. The main purpose of this study is to compare infiltration models used to assess the infiltration rate of the Mitidja Plain in Algeria. Field infiltration tests were conducted at 40 different sites using a double ring infiltrometer. Five statistical comparison criteria including root mean squared error (RMSE), normalized root mean squared error (NRMSE), coefficient of correlation (CC), Nash-Sutcliffe efficiency (NSE), and Kling-Gupta efficiency (KGE) were used to determine the best performing infiltration model and to confirm anomalies between predicted and observed values. We then evaluated the performance of five models (i.e., the Philip model, Kostiaikov model, Modified Kostiaikov model, Novel model, and Horton model) in simulating the infiltration process based on the adjusted performance parameters cited above. Results indicated that the Novel model best simulated the water infiltration process in the Mitidja Plain in Algeria, while the Philip model was the weakest for simulating the infiltration process. The conclusions of this study can be useful for estimating infiltration rates at various sites using the Novel model when measured infiltration data are not available, and are useful for planning and managing water resources in the study area.

Keywords: infiltration rate; infiltration model; double ring infiltrometer; Mitidja Plain; Novel model

Citation: Amina MAZIGHI, Hind MEDDI, Mohamed MEDDI, Ishak ABDI, Giovanni RAVAZZANI, Mouna FEKI. 2023. Estimation and inter-comparison of infiltration models in the agricultural area of the Mitidja Plain, Algeria. *Journal of Arid Land*, 15(12): 1474-1489. <https://doi.org/10.1007/s40333-023-0037-0>

1 Introduction

Infiltration refers to the process of water entering the soil or rock layers from the surface. This phenomenon can occur naturally, for example, through precipitation, or it can be facilitated through human activities such as irrigation or watering plants (Angelaki et al., 2021). Infiltration of water into the unsaturated zone is one of the most important components of the hydrologic cycle (Iovino et al., 2017). Over the last few decades, several physical and empirical models have been developed to quantify the infiltration process, particularly for one-dimensional vertical infiltration (Mishra et al., 2003). The Richards (1931) equation is one of the classic physical models for calculating semi-infinite,

isotropic, and stable soil infiltration processes. Infiltration rate depends on the nature of the soil (proportions of sand, silt, and clay) and the mineralogy of clay. Water moves faster through the large pores of sandy soil than through the small pores of clay, especially when the clay is compacted and has little or no structure or aggregation (Schumann, 1998). These soil infiltration properties are determined when mathematically fitting an infiltration model (Thomas et al., 2020).

However, not all infiltration models are suitable for all soils (Oku and Aiyelari, 2011). Many researchers compare the accuracy of different models by comparing calculated and observed infiltration rates. Under different conditions, a particular model will show better prediction than others, but so far there is no explicit mention of which model gives the best prediction (Kumar and Sihag, 2019). Many studies have compared different infiltration models. The Kostiakov and modified Kostiakov models were the most efficient in estimating the infiltration rate and cumulative infiltration, respectively. The Kostiakov model was most suitable for assessing plain in the Okhlal landfill, Delhi, India. The ability of a new infiltration model to estimate infiltration from actual field data was investigated in comparison with the Philip, Kostiakov, Horton, SCS, and modified Kostiakov models under similar conditions (Jain and Chakma, 2023).

Infiltration plays a crucial role in irrigation because it determines how efficiently water is absorbed by the soil and made available to crops. If the infiltration rate is too slow, water can pool on the surface and cause runoff, which can lead to soil erosion and water loss (Adeniji et al., 2013). On the other hand, if the infiltration rate is too fast, water may not be retained in the soil long enough for plants to absorb it, resulting in water stress for crops. By measuring and managing infiltration, farmers can optimize their irrigation practices and ensure that water is used effectively and efficiently to promote crop growth and yield (Thomas et al., 2020).

This research aims to experimentally estimate and compare soil infiltration rates in the Mitidja Plain in Algeria using five different infiltration models: Novel, Kostiakov, modified Kostiakov, Philip, and Horton. For this study, a number of specific sites within the region were selected and samples were collected from those sites. The infiltration rate was determined by a double ring infiltrometer. Statistical analyses were performed to compare infiltration models and observed infiltration rates. This study is the first step in a project aimed to improve irrigation water use and evaluate irrigation systems in the Mitidja Plain.

The Mitidja Plain is a traditional irrigation area originally composed of colonial lands devoted to viticulture and arboriculture. It is considered one of the most fertile areas of Algeria and of the entire world due to its agricultural production. Water consumption in the agricultural sector of the plain represents almost 70% of the total volume of mobilized water, which is a considerable volume given the current situation of water resources (Meddi and Eslamian, 2020), as in other regions of the world. This situation is prompting decision-makers to find more economical techniques to cope with climate change and the overexploitation of

groundwater. In order to develop innovative techniques and approaches, it is essential to study the evolution of infiltration into the ground in order to set up intelligent control and irrigation systems. Understanding infiltration in agricultural soils is an important phase in the design, evaluation, and management of furrow irrigation (Esfandiari and Maheshwari, 1997).

2.1 Study Area

The Mitidja Plain is located in the north of Algeria, facing the Mediterranean Sea in the northeast ($36^{\circ}22'30''$ – $36^{\circ}48'58''$ N, $02^{\circ}32'07''$ – $03^{\circ}28'14''$ E; 300 m a.s.l.). It is one of the main agricultural plains in the Mediterranean Basin, with a total area of nearly 1700 km² and agricultural areas ranging from 120×10^3 to 130×10^3 hm². It extends from the Wadi Nador in the west, bordered by the Dahra Mountains, east of the Oued Boudouaou, from the foothills of the Atlas Blidéen to the Sahel Mountains in the south, and the Bouzaréah Massif in the north (Bouziane et al., 2021). Administratively, it includes four cities: Algiers, Blida, Boumerdes, and Tipaza.

A Mediterranean climate prevails over the Mitidja Plain. Summers are hot and dry, and winters are rainy. The average winter temperature is 6°C, the average summer temperature is 33°C, and the average annual precipitation is 500–700 mm. The wet season is from October to May and the dry season is from June to September, and the estimated potential evapotranspiration in western and eastern Mitidja is about 1326 and 1271 mm, respectively (Boufekane et al., 2020). The hydrology of the study area is characterized by intense channel densities of four major rivers: Wadi Legaia, Wadi Hamiz, Wadi El Harrach in eastern Mitidja, and Wadi Mazafran in western Mitidja. The tributaries of these rivers originate from the Blidean Atlas and have considerable north-south flow. Figure 1 [Figure 1: see original paper] shows the experimental sites and soil texture. This area is characterized by fine and fertile soil. The most common soil texture is clay, and soils are dominated by alluvial and colluvial soils. Most farms are on alluvial soil.

2.2 Measurement of Infiltration Rate

To measure the infiltration rate, we used a double ring infiltrometer. This device measures the infiltration rate of water into soil and consists of two concentric rings 250 mm deep, with the inner ring (110 mm) being smaller than the outer ring (320 mm). The space between the two rings creates a circular trench (Fig. 2 [Figure 2: see original paper]). The rings are made of metal and are driven into the soil to 40 mm depth, leaving only the top edge of the rings exposed. Both rings were filled with water to equal depth, and the initial reading of the water level was noted. The depth of water in the inner ring of the infiltrometer

was noted at regular time intervals (1 min) until the rate of infiltration became steady. The infiltration rate is typically calculated as the volume of water that infiltrates into the soil per unit of time and surface area of the soil. The double ring infiltrometer is a useful tool for assessing the infiltration capacity of soil and can be used to evaluate the effectiveness of soil conservation measures, irrigation practices, and other land management practices (Soil Science Equipment | Double Ring Infiltration Surface Measure, 2020). It is particularly useful in agricultural areas where efficient water use is important.

2.3 Experimental Data

Soil samples were collected with core samplers to an average depth of 50 cm, and disturbed soil samples (40 points) were collected in the field at the site and air-dried, crushed, and passed through a 2-mm sieve to obtain soil fractions for soil texture determination. We used a textural classification triangle to classify the soil based on the results obtained from the analysis. Experimental tests were conducted individually for 40 sites (experimental samples; Fig. 1). The results of the analysis of soil physical properties and infiltration rate (initial and final) of the study area at each site are presented in Table 1. The results showed that the texture of sampled sites was predominantly clayey. The initial infiltration rate varies from 11.70 to 330.00 mm/h and the range of final infiltration rates was from 3.71 to 138.42 mm/h. Variations in infiltration rates are favored by the importance of root systems and animals digging into the soil, insufficient pre-wetting, and soil disturbance by the double rings infiltrometer.

2.4 Infiltration Models and Parameters

In this study, infiltration data were fitted to the infiltration models of Kostiakov, Philip, Horton, modified Kostiakov, and Novel.

2.4.1 Kostiakov Model

The Kostiakov model is commonly used in irrigation engineering and is derived using data observed in the field or in the laboratory (Parhi et al., 2007). Kostiakov (1932) proposed the following best-fit infiltration equation:

$$f(t) = a \times t^{-b}$$

where $f(t)$ is the infiltration rate (mm/h); a is the coefficient; t is the time (h); and b is the exponent. Both parameters rely on soil type, initial moisture content, rainfall rate, and vegetative cover, and these can be determined empirically.

2.4.2 Modified Kostiakov Model

The modified Kostiakov equation includes the term steady infiltration capacity (f_c ; mm/h). The parameter f_c is included because the infiltration rate decreases as more water penetrates the soil, eventually reaching a constant or final infiltration rate (Vand et al., 2018). The modified Kostiakov equation is expressed as follows:

$$f(t) = a \times t^{-b} + f_c$$

2.4.3 Philip Model

Philip and De Vries (1957) proposed a model based on a semi-analytical solution of the Richards flow equation (Richards, 1931). In this solution, Philip and De Vries (1957) used a time series to solve the Richards equation. Neglecting the higher order terms, we derived the results of a two-term infiltration equation in which both parameters have physical meanings (Zakwan et al., 2016).

$$f(t) = \frac{1}{2}St^{-0.5} + K$$

where S is the Sorptivity parameter that is the function of soil matrix forces (mm/h^{-0.5}); and K is the soil parameter related to transmission of water through soil or gravity force.

2.4.4 Horton Model

The Horton equation is one of the most popular empirical models simulating water infiltration into soils (Dahak et al., 2022). The infiltration equation is a three-parameter equation that is expressed as follows:

$$f(t) = f_c + (f_0 - f_c) \times e^{-kt}$$

where f_0 is the initial infiltration rate (mm/h); f_c is the final infiltration rate (mm/h); e is the mathematical constant; and k is the rate constant in the dimension of time t (1/t).

2.4.5 Novel Model

A typical non-linear regression model developed from the modified Kostiakov model (Sihag et al., 2017) was adopted, as shown below:

$$f(t) = a \times t^{-b} + cf_c$$

where c is the coefficient.

2.5 Statistical Comparison Criteria

2.5.1 RMSE

RMSE is one of the most commonly used measures of prediction quality. It shows how far the predictions deviate from actual measured values (Bennett et al., 2013). RMSE is a good measure of accuracy, but only for comparing the prediction errors of different models or model configurations for a particular variable, not between variables.

$$\text{RMSE} = \sqrt{\frac{\sum_{i=1}^n (a_i - b_i)^2}{n}}$$

where a_i is the simulated value; b_i is the observed value of infiltration rate; and n is the number of observations.

2.5.2 NSE

The NSE criterion of Nash and Sutcliffe (1970) was introduced as a measure of model performance. The NSE criterion better reflects the desirable and undesirable properties of the model of interest and increases as the quality of the model improves. NSE can be defined as follows:

$$\text{NSE} = 1 - \frac{\sum_{i=1}^n (a_i - b_i)^2}{\sum_{i=1}^n (b_i - \bar{b})^2}$$

where \bar{b} is the average of observed values. For nonlinear models, NSE can be negative. In fact, it ranges from $-\infty$ to 1. As usual (Zeybek, 2018), researchers look for NSE values close to 1. Negative values indicate unacceptable model performance. This is one of the recommended model performance metrics in hydrology as well as many other applications.

2.5.3 KGE

KGE fills several gaps in NSE and is increasingly used for model calibration and evaluation.

$$\text{KGE} = 1 - \sqrt{(r - 1)^2 + (B - 1)^2 + (C - 1)^2}$$

where r is the linear correlation coefficient between observed and computed values; B is the ratio between SD of simulated flows and SD of observed flows; and C is the ratio between mean simulated flow and mean observed flow (Knoben et al., 2019). This coefficient is more accurate than NSE.

2.5.4 CC

CC is a statistical measure that calculates the strength of relationship between movements of two variables (Lei et al., 2020). CC is calculated as follows:

$$CC = \frac{\sum_{i=1}^n (a_i - \bar{a})(b_i - \bar{b})}{\sqrt{\sum_{i=1}^n (a_i - \bar{a})^2 \sum_{i=1}^n (b_i - \bar{b})^2}}$$

2.5.5 NRMSE

NRMSE makes it easy to compare models at different scales. NRMSE refers to RMSE of observed range of variables (Tadj et al., 2014). Therefore, NRMSE can be interpreted as part of the total range normally resolved by the model.

$$NRMSE = \frac{RMSE}{b_{\max} - b_{\min}}$$

2.5.6 Percent Bias (PBIAS)

PBIAS measures the average tendency of simulated values to be larger or smaller than observed values (Golmohammadi et al., 2014).

$$PBIAS = 100 \times \frac{\sum_{i=1}^n (a_i - b_i)}{\sum_{i=1}^n b_i}$$

3.1 Model Parameters

To estimate infiltration rates in our study area, we opted for the Novel, Kostikov, modified Kostikov, Philip, and Horton models. Observed field data on infiltration rates were used to evaluate these models, and numerical values for the infiltration equation parameters were obtained. The obtained model parameters and statistical parameters were calculated using the Rtop package of R statistical software.

A comparative analysis of soil water-infiltration characteristics for ten different classes of soil was performed. The estimated parameter values for the five selected infiltration models are listed in Table 2. The values of b_i for the Novel, Kostikov, and modified Kostikov infiltration models showed significant similarity across the ten soil types. In contrast, parameters f_c were completely different in the Novel, Horton, and modified Kostikov models due to other parameters such as c in the Novel model and k in the Horton model. These empirical parameters have soil physical meaning. A size comparison of each of the model parameters indicated that there is no relationship between the parameter k in the Horton model and the Philip model. The parameter a_i in the modified

Kostiakov model is similar to that in the Novel model; however, this is not the case in the Kostiakov model.

Individual infiltration curves were generated from experimental tests. Results of the field infiltration rates and simulated infiltration rates for the five models for each soil class are presented in Figure 3 [Figure 3: see original paper]. The graphics showed that the observed infiltration data took 35 min to 3 h to reach the steady infiltration rate.

The Philip model had the highest deviations because it overestimated the data measured at sampling points P1 and P15. The Horton model had the second lowest performance after the Philip model. This may be due to the fact that their parameters do not have a consistent physical interpretation and that the process involved in evaluating the parameters can be very sensitive to approximation errors.

For clay-sandy, fine-clay-loam, clay-loam, and clay soils, the Horton and Philip models deviated from the observed data, while the modified Kostiakov and Novel models provided a better fit. For fine-silty and very fine-silty soils, it was difficult to decide which model gave the best performance, so the performance parameters were used to make a better comparison. However, the infiltration rate estimated by the Novel model was the most effective in predicting the fit of the experimental data measured at all sampling points.

3.2 Performance Parameters

Statistical criteria such as RMSE, NRMSE, CC, NSE, and KGE were used to evaluate infiltration models. We selected the best model based on the following criteria: maximum CC, minimum RMSE, minimum NRMSE, maximum NSE, and maximum KGE. The results shown in the box plot (Fig. 4 [Figure 4: see original paper]) were computed for different models and the values are shown in Table 3 .

The KGE and NSE values were close to 1.00, with intervals of 0.90-0.99 and 0.80-0.98, respectively, for the Horton model in sandy clay, clay-loam, and sandy loam soils. This indicates that the Horton model can predict the infiltration rate for these soil classes. For the remaining soil classes, the Novel model had the highest values, between 0.85 and 0.99, for both parameters.

The NRMSE values for the Philip model were unacceptable, ranging from 0.03 to 0.35. In contrast, the Novel model had the best results, with NRMSE values ranging from 0.01 to 0.19. The Kostiakov and modified Kostiakov models produced good results compared with the Philip model, with the KGE and NSE values ranging from 0.57 to 0.99 and 0.15 to 0.99, respectively, for both models. The NRMSE values for the Kostiakov and modified Kostiakov models ranged from 0.03 to 0.43 and 0.02 to 0.19, respectively.

The KGE parameter in Figure 4a showed that the Novel and modified Kostiakov models had the median value closest to the ideal value of 1.00, with a range of 0.91-0.99 and five outliers for both models. In contrast, the Philip model had the largest value ranging from 0.84 to 0.93, with three outliers. The Horton model had a uniform distribution ranging from 0.91 to 0.99, with two outliers.

For the NSE parameter in Figure 4b, the modified Kostiakov and Novel models gave the same results, with a range of 0.85-0.98 and five outliers. The Kostiakov model had the largest value ranging from 0.75 to 0.97, with only one outlier. Like the KGE parameter, the Horton model had a uniform distribution ranging from 0.83 to 0.97, with two outliers. Finally, for the NRMSE parameter in Figure 4d, the Novel and modified Kostiakov models gave the best results compared with the other infiltration models, approaching the ideal value of 0.00 with a range of 0.02-0.14. The Philip model had the highest uncertainty, with a range of 0.06-0.16, followed by the Kostiakov model (0.05-0.12) and the Horton model (0.05-0.12) in terms of estimating infiltration rate values. The Novel and modified Kostiakov models performed the best in terms of all three statistical criteria (KGE, NSE, and NRMSE), and the Philip model performed the worst.

The Novel model explained almost all the variability in the data, as indicated by its high KGE and NSE values and low NRMSE value. A comparison of the statistical parameters shows that the Novel model fits well with the measured data for all types of soil except sandy clay, clay-loam, and sandy loam soils, where the Horton model performed better.

Figure 5 [Figure 5: see original paper] shows the PBIAS errors for different infiltration models. The Novel and modified Kostiakov models had the lowest PBIAS errors, ranging from -12% to 12%, with most of the values concentrated around 0%. The Philip model had the largest PBIAS errors, ranging from -20% to 20%, with a significant number of values concentrated around 5%. The Kostiakov model had an asymmetric PBIAS distribution, ranging from -27% to 15%, similar to the Horton model (-15%-20%). Therefore, we can conclude that the Novel model has the best fit to the measured data, as it is the closest to the ideal value of 0% for PBIAS error. This is likely because the Novel model is developed from the modified Kostiakov model. The Novel model outperformed the other infiltration models in terms of statistical criteria and PBIAS error. It is therefore the most suitable model for predicting infiltration rates for a variety of soil types.

4 Discussion

In the context of our current research, we applied infiltration models across ten distinct soil types with the primary aim of evaluating the performance of five infiltration models when compared with observed data. This comprehensive analysis allowed us to gain valuable insights into the effectiveness of these models in accurately predicting infiltration characteristics in a diverse range of

soils. The results of our study, which are presented in Table 3 and Figures 4 and 5, demonstrated the superiority of the Novel model in replicating observed experimental data. This model demonstrated remarkable success in forecasting infiltration behavior in seven different soil types with exceptional accuracy. It is important to note that while the Novel model excelled for the majority of soil types, three exceptions were identified—namely sandy clay, clay-loam, and sandy loam soils—which were best characterized by the Horton model.

This finding aligns with the results of Singh et al. (2018), who predicted cumulative infiltration rate under inceptisols in tropical dry brown soils and found the Novel and modified Kostiakov models to be more suitable than the Kostiakov and SCS (soil conservation service) models. Furthermore, our assessment encompassed a broader scope, extending to the region of Lafia in North Central Nigeria, where four distinct infiltration models were evaluated: the Kostiakov, modified Kostiakov, Philip, and Horton models. In this specific context, the Horton model emerged as the most suitable fit for measured cumulative infiltration rate, as affirmed by Ogbe et al. (2011). This particular finding holds significance for the practical application of infiltration modeling in that region.

Additionally, Wang et al. (2017) concluded that the Mezenzev and Horton models offer a more accurate description of the relationship between cumulative infiltration and infiltration time when biochar is introduced into the soil. Moreover, as deduced by Duan et al. (2010), the Mezenzev and Horton models surpassed the other three infiltration models in terms of performance. Their research provided the most accurate depiction of the intricate relationship between cumulative infiltration and infiltration time within lawn soils. This finding underscores the superior capabilities of the Mezenzev and Horton models, shedding light on their ability to offer a more precise representation of infiltration rate.

It should be noted that the result of Duan et al. (2010) closely mirrors our findings for sandy clay, clay-loam, and sandy loam soils, where the Horton model exhibited a superior fit when compared with the Novel model. This intriguing consistency in results further gains support from parallel experiments conducted at the Agricultural Research Farm of the Bahauddin Zakariya University in Multan, Pakistan, as detailed by Farid et al. (2019). Their research involved the assessment of three distinct infiltration models: the Kostiakov, Philip, and Horton models. Their results reinforce the effectiveness of the Horton model in accurately describing infiltration behavior. Moreover, Rasool et al. (2021) found that the modified Kostiakov model consistently outperforms other models in terms of infiltration predictions. Our study also confirmed its modeling power except for the Horton model. These results underscore the necessity of thoroughly assessing and documenting the performance of various infiltration models at specific locations.

Haghighi et al. (2010) emphasized the importance of evaluating each model's ability to estimate final infiltration rates at different geographic sites. Such location-specific evaluations are essential in modeling infiltration to meet the unique requirements of individual regions. Indeed, the applicability of infiltra-

tion models is not universal, as demonstrated by Machiwal et al. (2006) and Oku and Aiyelari (2011). Their work affirms that one or more infiltration models may be better suited for a particular location, further reinforcing the idea that not all models are universally suitable for all soil types and geographic settings.

The Novel model serves as a valuable tool for generating infiltration data specifically tailored to the soils within the Mitidja Plain. The insights gained from this work contribute to the broader goal of enhancing water resource management in the Mitidja Plain. The enhanced modeling provided by this research offers a more comprehensive understanding of water flow dynamics, which is vital for safeguarding the region against flooding and ensuring the efficient use of water resources. In summary, the Novel model's capacity to generate infiltration data tailored to the Mitidja Plain's soils has far-reaching implications.

5 Conclusions

Infiltration models have become one of the most important tools for managing water resources. In this work, an attempt was made to validate the predictive accuracy of five infiltration models using measurements from a double ring infiltrometer. A comparison of field and predicted infiltration rates showed that the Novel model-predicted infiltration rates were much closer to the observed data. The NRMSE and KGE results show that the infiltration rate can be predicted by the Novel, modified Kostiaikov, Horton, Kostiaikov, and Philip models. Based on the mean NRMSE values, we concluded that the Novel model provided the lowest values and that the infiltration was adequately described by this model. As shown by the results, the Novel model had the lowest PBIAS in predicting infiltration rates. Thus, in the absence of measured infiltration data, the Novel model can be used to generate infiltration information for the Mitidja Plain and other plains in northern Algeria and North Africa.

Conflict of Interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Acknowledgements

This study was conducted by the Water and Environment Engineering Laboratory (GEE) of the Higher National School of Hydraulics (ENSH), and this study is carried out within the framework of the SWATC project (Prima project) funded by the DGRSDT, Algeria.

Author Contributions

Conceptualization: Amina MAZIGHI, Mohamed MEDDI; Methodology: Amina MAZIGHI, Mohamed MEDDI, Giovanni RAVAZZANI, Mouna FEKI; Formal analysis: Amina MAZIGHI, Mohamed MEDDI, Ishak ABDI; Writing - original draft preparation: Amina MAZIGHI, Mohamed MEDDI, Hind MEDDI; Writing - review and editing: Amina MAZIGHI, Hind MEDDI; Funding acquisition: Mohamed MEDDI, Hind MEDDI; Resources: Amina MAZIGHI, Mohamed MEDDI, Giovanni RAVAZZANI, Mouna FEKI, Ishak ABDI, Hind MEDDI; Supervision: Mohamed MEDDI, Hind MEDDI.

References

- Adeniji F A, Umara B G, Dibal J M, et al. 2013. Variation of infiltration rates with soil texture: A laboratory study. *International Journal of Engineering and Innovative Technology*, 3(2): 454-459.
- Angelaki A, Singh Nain S, Singh V, et al. 2021. Estimation of models for cumulative infiltration of soil using machine learning methods. *ISH Journal of Hydraulic Engineering*, 27(2): 162-169.
- Bennett N G, Croke B F W, Guariso G, et al. 2013. Characterising performance of environmental models. *Environmental Modelling and Software*, 40: 1-20.
- Boufekane A, Meddi H, Meddi M. 2020. Delineation of groundwater recharge zones in the Mitidja Plain, North Algeria, using multi-criteria analysis. *Journal of Hydroinformatics*, 22(6): 1468-1484.
- Boufekane A, Yahiaoui S, Meddi H, et al. 2021. Modified DRASTIC index model for groundwater vulnerability mapping using geostatistic methods and GIS in the Mitidja Plain Area (Algeria). *Environmental Forensics*, 23(5-6): 539-556.
- Bouziane O, Mohamed M, Juan Reza C. 2021. Characterization of the water holding capacity of the soils in the Mitidja Plain (Algeria) as a basis for the development of the irrigation water use. *Journal of Taiwan Water Conservancy*, 69(4): 27-39.
- Dahak A, Boutaghane H, Merabtene T. 2022. Parameter estimation and assessment of infiltration models for Madjez Ressoul Catchment, Algeria. *Water*, 14(8): 1185, doi: 10.3390/w14081185.
- Duan R B, Clifford B F, John B. 2010. Field evaluation of infiltration models in lawn soils. *Irrigation Science*, 29(5): 379-389.
- Esfandiari M, Maheshwari B L. 1997. Application of the optimization method for estimating infiltration characteristics in furrow irrigation and its comparison with other methods. *Agricultural Water Management*, 34(2): 169-185.
- Farid H U, Mahmood-Khan Z, Ahmad I, et al. 2019. Estimation of infiltration models parameters and their comparison to simulate the onsite soil infiltration

characteristics. *International Journal of Agricultural and Biological Engineering*, 12(3): 1-8.

Golmohammadi G, Prasher S O, Madani A, et al. 2014. Evaluating three hydrological distributed watershed models: MIKE-SHE, APEX, SWAT. *Hydrology*, 1(1): 20-39.

Haghighi F, Gorji M, Shorafa M, et al. 2010. Evaluation of some infiltration models and hydraulic parameters. *Spanish Journal of Agricultural Research*, 8(1): 210-218.

Iovino M, Angulo-Jaramillo R, Bagarello V, et al. 2017. Thematic issue on soil water infiltration. *Journal of Hydrology and Hydromechanics*, 65(3): 205-208.

Jain L, Chakma S. 2023. Effects of temperature and slope on the infiltration rate for a landfill surface. *Current Science*, 124(1): 1-8.

Knoben W J M, Freer J, Woods R. 2019. Technical note: Inherent benchmark or not? Comparing Nash-Sutcliffe and Kling-Gupta Efficiency Scores. *Hydrology and Earth System Sciences*, 23(10): 4323-4331.

Kumar M, Sihag P. 2019. Assessment of infiltration rate of soil using empirical and machine learning-based models. *Irrigation and Drainage*, 68(3): 588-601.

Lei G H, Fan G L, Zeng W J, et al. 2020. Estimating parameters for the Kostikov-Lewis infiltration model from soil physical properties. *Journal of Soils and Sediments*, 20(1): 166-180.

Machiwal D, Jha M K, Mal B C. 2006. Modelling infiltration and quantifying spatial soil variability in a wasteland of Kharagpur, India. *Biosystems Engineering*, 95(4): 569-582.

Meddi M, Eslamian S. 2021. Uncertainties in rainfall and water resources in Maghreb countries under climate change. In: Leal Filho W, Oguge N, Ayal D, et al. *Handbook of Climate Change Adaptation*. Cham: Springer, 1967-2003.

Mishra S K, Tyagi J V, Singh V P. 2003. Comparison of infiltration models. *Hydrological Processes*, 17(13): 2629-2652.

Ogbe V B, Jayeoba J O, Ode S O. 2011. Comparison of four soil infiltration models on a sandy soil in Lafia, southern guinea savanna zone of Nigeria. *Production Agricultural and Technology*, 7: 116-126.

Oku E, Aiyelari A. 2011. Predictability of Philip and Kostikov infiltration models under inceptisols in the humid forest zone, Nigeria. *Kasetsart Journal-Natural Science*, 45(4): 604-611.

Parhi P K, Mishra S, Singh R. 2007. A modification to Kostikov and Modified Kostikov infiltration models. *Water Resources Management*, 21(11): 1973-1989.

Philip J R, De Vries D A. 1957. Moisture movement in porous materials under temperature gradients. *Transactions, American Geophysical Union*, 38(2): 222-

232.

Rasool T, Dar A, Wani M A. 2021. Comparative evaluation of infiltration models under different land covers. *Water Resources*, 48(4): 624-634.

Richards L A. 1931. Capillary conduction of liquids through porous mediums. *Physics*, 1(5): 318-333.

Schumann A H. 1998. Infiltration: Introduction. In: Herschy R W, Fairbridge R W. *Hydrology and Lakes*. Encyclopedia of Earth Science. Dordrecht: Springer, 418.

Sihag P, Tiwari N K, Ranjan S. 2017. Estimation and inter-comparison of infiltration models. *Water Science*, 31(1): 34-43.

Singh B, Sihag P, Singh K P. 2018. Comparison of infiltration models in NIT Kurukshetra campus. *Applied Water Science*, 8(2): 1-9.

Soil Science Equipment | Double Ring Infiltrometer Surface Measure. 2020. SDE Council. [2022-10-22]. <https://environnement.sdec-france.com/double-ring-infiltrometer-for-soil-science.html>.

Tadj M, Benmouiza K, Cheknane A, et al. 2014. Improving the performance of PV systems by faults detection using GISTEL approach. *Energy Conversion and Management*, 80: 298-304.

Thomas A D, Ofosu A E, Amuzu E, et al. 2020. Comparison and estimation of four infiltration models. *Open Journal of Soil Science*, 10(2): 45-57.

Vand A S, Sihag P, Singh B, et al. 2018. Comparative evaluation of infiltration models. *KSCE Journal of Civil Engineering*, 22(10): 4173-4184.

Wang T T, Stewart C E, Ma J B, et al. 2017. Applicability of five models to simulate water infiltration into soil with added biochar. *Journal of Arid Land*, 9(5): 701-711.

Zakwan M, Muzzammil M, Alam J. 2016. Application of spreadsheet to estimate infiltration parameters. *Perspectives in Science*, 8: 702-704.

Zeybek M. 2018. Nash-Sutcliffe efficiency approach for quality improvement. *Journal of Applied Mathematics and Computation*, 2(11): 496-503.

Note: Figure translations are in progress. See original paper for figures.

Source: ChinaXiv – Machine translation. Verify with original.